


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SW 1/4 SW 1/4 NE 1/4	11	T 28 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

Approximately 1/8 mile south and 1/8 mile east of Wichita

2 WATER WELL OWNER:	Boeing Company	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	3801 S. Oliver	Application Number: N/A
City, State, ZIP Code :	Wichita, KS 67210	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 43.5 ft. ELEVATION: unknown
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 22.3 ft. below land surface measured on mo/day/yr 11-10-92
	Pump test data: Well water was not ch'd ft. after hours pumping gpm
	Est. Yield unknown gpm Well water was ft. after hours pumping gpm
	Bore Hole Diameter 11 in. to 43.5 ft. and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	Recovery
Was a chemical/bacteriological sample submitted to Department? Yes No X	If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below)	Welded
2 PVC 4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5 in. to 20 ft. Dia in. to ft. Dia in. to ft.		
Casing height above land surface 24 in. weight 2.87 lbs./ft. Wall thickness or gauge No. 26.5		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 20 ft. to 41.5 ft. From ft. to ft.		
GRAVEL PACK INTERVALS: From 18 ft. to 43.5 ft. From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug
Grout Intervals: From ft. to ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	Ground already
Direction from well?	How many feet? contaminated

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Fill			
5	8.5	Clay, light yellow, tan			
8.5	12	Clay, light brown, little gray			
12	19	Clay, light brown, real soft, little sandy			
19	23	Clay, light brown, little sand and gravel, real thin			
23	25	Clay, olive green and light tan			
25	26	Sand			
26	27	Sandstone			
27	33	Sand			
33	40.5	Clay, olive gray			
40.5	43.5	Shale, dark gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-13-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 2-25-93 under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]
