1 LOCATION OF WATER WELL:				raction							n Numb	er	Townsh	hip Number		Range Nun		ber	]
	Sedç							SW			10	Т		28	S	R	1	E	
Distance and	direction from	m nearest	town or	city stre	et addre	ess of v	vell if l	ocated w	thin ci	ty?									
	andfill, 60'										Vichita	•							-
	WELL OWNE	-			Depa	rtmei	nt of	Public	: WO	rks									
	dress, Box#											В	oard of	Agricul	ture, Div	ision of '	Water Re	sources	
City, State, Z	ZIP Code	: Wic	hita, K	S 67	202							A	pplicati	on Num	ber:				1
3 AN "X" IN	WELL'S LOC I SECTION B	OX. OX.	111 4	DEPTH	OF COI	MPI FT	FD W	FII		5	ft FI	FVATIO	)Ni-						
<b>A</b>	1	T	Der	oth(s) Gr	oundwa	ter En	counte	red 1				ft 2			ft	 ব		ft	1 ⊆
	NW																		
	: T	- NE	1																}
₩			E Fet	Yield	i ump to	ann	. W	ell water	was			ft ofte	" ir		houre	umping	, ,	gpm	CSE
7		<b> </b>	Bor	e Hole [	)iamete	- ab	8	in to	***	5		ft a	" nd	••	110013	o to		gpiii	2
	¿X	- SE	WE	LL WAT	ER TO	BE ŪS	ED AS	5: 5 Pî	blic w	ater su	oply	" 21	Air co	nditioni	ng 1	1 Inject	tion well		ONLY
	j	_i		1 Don	nestic	3 Fee	d lot	6 Oi	l field v	water s	upply	9	Dewa	tering	1	2 Othe	(Specify	/ below)	
▼				2 Irrig	ation	4 Indi	ustrial	7 La	wn an	d garde	n (dome	estic) 1	0 Mon	itoring v	well	Soil Va	por Extr	action	_
	S		Wa	s a cher	nical/ba	cteriolo	gical	sample s	ubmitte	ed to De	epartmei	nt? Yes		No X	If yes	, mo/da	y/yr samp	le was	1
			sub	mitted								Water W	ell Disi	nfected	? Yes		No X		
5 TYPE OF	BLANK CAS	SING USE	D:			5 Wro	ought I	lron	8 (	Concre	te tile	(	CASING	JOINT	S: Glue	d	Clamp	ed	
1 Ste	el	3 RN	MP (SR)			6 Ast	estos	-Cement											
2 PV	C	4 AB	ss			7 Fib	erglas	s					Γ		Threa	ded	Flu	sh	1
Blank casing	diameter	<b>–</b> 4	in.	to	2	ft.	. Dia												1
Casing heigh	ht above land	surface		30	in	. weial	nt.		.703		lbs.	/ft. Wall	thickne	ess or a	auge No		SCH.	40	
	CREEN OR P					.,g.									tos-cem				1
1 Ste						5 Fib	eralas										. <b></b>		
2 Bra		4 Ga	alvanized	steel		6 Coi	ncrete	tile		9 /	ABS	•,	12	None	used (op	en hole	)		
	R PERFORAT	TION OPE	NINGS	ARE:			5	Gauze	d wra	pped		8	Saw cu	ut		11 No	one (open	hole)	
1 Cor	ntinuous slot		3 Mill	slot				Wire v				9	Drilled	holes					
2 Lou	vered shutter							Torch				10	Other	(specif	y)				
SCREEN-PE	ERFORATED	INTERVA	ALS:	From		2	ft.	to		5	f	ft. From			ft.	to		ft.	
GRA	AVEL PACK I	NTERVAL	.S:	From		1	ft.	to		5	f	ft. From			ft.	to		ft.	1
				From				to											
6 GROUT	MATERIAL:	1 Ne							T	3 Bent	onite	4.0	ther		W-1				7
Grout Interv	als From	0	ft to	•	1	ft F	rom			ft to	`		ft. F	rom		ft t		 #	1
What is the	nearest source	e of possi	ble conta	aminatio	* n·	- ". '				". "	10 Li	vestock	nens				ed water w		
	otic tank	4				7	Pit privy				uel stora			15 Oi					
2 Sewer lines								Sewage				ertilizer s	•				ecify belov	w)	
3 Wa		Seepag				Feedyar	•			secticide	-				,	,			
Direction fro	-				•			•				any feet	•						
FROM	ТО	CODE		Lľ	THOLO	GIC LC	)G		F	ROM	TÖ			PLU	GGING I	NTERV	ALS		
0	1		Clay																_
1	5		Sand						<u> </u>										
									-										-
									-			-							-
				· .		14			+									•	$\dashv$
									+-		-								$\dashv$
	***								+										$\dashv$
						•													
									1.										
									-										
7 00:	L								1								-		4
	ACTOR'S OR		VNER'S				s wate	r well was	s (1) c	onstruc	ted, (2) ı	reconstru	ucted, o	r (3) plu	gged und	der my ju	urisdiction	and was	•
	on (mo/day/yr)				06/28												d belief.		
Water Well	Contractor's L	icense No				531											) 08/1	1/08	
	usiness name							s Inc.		by	(signatu	ire)	25	1.11	totas				
	UCTIONS:. Plon St., Ste. 420,																	00 S W	
		. upona, N					20	2 00-10.	311G UI	.5 10 117		OVVIN		. Ctan i Ol	you		<u></u>		