

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4 SW 1/4 SW 1/4		5		T 28 S		R 1 E	
Distance and direction from nearest town or city street address of well if located within city?									
2796 S. Seneca, Wichita									
2 WATER WELL OWNER:		TOTAL Petrochemicals USA, Inc.							
RR#, St. Address, Box #		1201 Louisiana St., Suite 1800							
City, State, ZIP Code		Houston, TX 77002							
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 26 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1 ft 2 ft 3 ft							
		WELL'S STATIC WATER LEVEL 14.09 ft. below land surface measured on mo/day/yr 11/18/2009							
		Pump test data: Well water was NA ft. after hours pumping gpm							
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8 in. to 26 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Air sparge							
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 2 in. to 24 ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No. Sch. 40							
TYPE OF SCREEN OR PERFORATION MATERIAL		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 24 ft. to 26 ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 12 ft. to 26 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 11 ft. From 11 ft. to 12 ft. From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS		0 8 Sand and clay, interbedded,							
8 12 Sand, fine to med.,		12 26 Sand, med. to coarse,							
		AS1, Flushmount							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/20/2009 and this record is true to the best of my knowledge and belief.		Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 11/18/2009 under the business name of GeoCore, Inc. by (signature) Dale Kelly							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									