

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SE 1/4 SW 1/4	SECTION NUMBER 16	TOWNSHIP NUMBER T 28 S	RANGE NUMBER R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 47th South & Santa Fe (2 logs on 1 permit) Wichita, Kansas				
2 WATER WELL OWNER: WICHITA, CITY OF		Board of Agriculture, Division of Water Resource		
RR#,ST. ADDRESS,BOX #: 455 N. Main				
CITY, STATE:	Wichita, Kansas	ZIP CODE:	Application Number: 20090287	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NW NE S W SE S 1 Mile W E	4 DEPTH OF COMPLETED WELL: 40 ft.			
	ELEVATION:			
Depth of groundwater Encountered: _____ ft.				
WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 11/24/09				
Pump test data:	Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
Est. Yield: _____ gpm	Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
Bore Hole Diameter 12 in.	to 40 ft.	and _____ in.	to _____ ft.	
WELL WATER TO BE USED AS:				
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well				
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)				
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO				
5 TYPE OF CASING USED:				
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded				
Blank casing diameter 8 in. to 20 ft., Dia. in. to ft., Dia. in. to ft.				
Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft. Wall thickness or gauge No. .332				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)				
SCREEN - PERFORATION INTERVAL From 20 ft. to 40 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 20 ft. to 40 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug				
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well				
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent				
Direction from well? From To LITHOLOGIC LOG From To LITHOLOGIC LOG				
0 3 topsoil				
3 19 fine sand				
19 40 medium sand				
RECEIVED				
DEC 21 2009				
BUREAU OF WATER				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 11/24/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/25/2009 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp				