WATER WELL RECORD			Form W	WC-5	Di	vision of Wate	r Resources App. No	0.	
1 LOCATION OF WATER WELL:			Fraction		Section	on Number	Township No.	Range Number	
Count	y:Seda	wick	1/4 NW 1/4 NW	32	2	T 28 S	R1 KXE □W		
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:									
from r	from nearest town or intersection: If at owner's address, check here . Latitude:								
Inter	Intersection Of Seneca & Karla Streets, Haysville, KSLongitude: (in decimal degrees)								
	Elevation:								
A XX/A/7	TED XX	TI OWNER					4, 🔲 NAD 83, 🔲	NAD 27	
2 WATER WELL OWNER: Hampton & Sons Construction						Collection Method:			
RR#, Street Address, Box #: 1912 E. Diedrich City, State, ZIP Code : Haverillo RC 67060						☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City,	State, Z	^{IP Code} : Haysvil	le, KS 67060						
Est. Accuracy:									
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 300 x 7 holes ft.									
	ION BO	X: Depth(s) Groundwater Encountered (1)							
	N	Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL ft. ft. below land surface measured on mo/day/yr.							
		Pump test data: Well water wasft. after hours pumping gpm							
		ECT VIELD 17/2 cmm Well water was 4 short hours numbing com							
w NW	- NW NE EST. FIELD. AN. 9. gpm. Well water was								
1 1	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
		Domestic							
l sw	3	☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No									
S If yes, mo/day/yr sample was submitted									
1 mile Water well disinfected? ☑ Yes ☐ No									
5 TYPE OF CASING USED: Steel PVC Tother .Polyethyleneloops									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter									
Casing height above land surface. 0 in., Weight									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
Steel Stainless Steel PVC Other (Specify)									
☐ Brass ☐ Galvanized Steel ★ None-used (open-hole) Geothermal Closed loop system x 7 holes									
SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From to tt., From tt. to tt. From ft. to ft., From ft. to ft.									
6 CROUT MATERIAL: Nest cement Coment grout Reptonite Cother									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
What is the nearest source of possible contamination:									
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)									
Sewer lines									
 	Watertigl	nt sewer lines	it 🔲 Feedyard [Fertilizer	storage	Oil well/ga	s well		
		well East				ell1.00.			
FROM	ТО	LITHOLOG	IC LOG	FROM	ТО	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
0	3	Topsoil							
3	6	Clay, sandy red							
6	54	Sand, fine to coa	rse with gravel						
54	110	Shale, gray							
110	210	Shale, gray with		.5					
210	300	Limestone (hard)	/shale layers						
					-				

	D 4 67-7-1	NICORY AND COMME	IO CEDAVEI C. T.	N. 671.		RP			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, □ reconstructed, or □ plugged									
under my jurisdiction and was completed on (mo/day/year)7/19/10 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/year)8/12/10									
under the business name of .Peterson .Irrigation, .Inc. by (signature)									
		Use typewriter or ball point pen. Kansas Department of Health							
		5522. Send one copy to WAT							
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212									