WATER WELL RECORD Form	WWC-5 K	(SA 82a-12	12		
□ a , , ,	SECTION NUMBE				
Sedgwick NW 1/4 NE 1/4 NE 1/4 Distance and direction from nearest town or city street address of well if located within city?	34	T 2	28 S	R 1E	E/W
6429 S. Cedar Dale  Wichita, Kansas					
2 WATER WELL OWNER: BLUE CUSTOM HOMES LLC					**
RR#,ST. ADDRESS,BOX #: 106 S. Breezy Pointe Circle			Board of Agri	culture, Division of W	ater Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:		Application Nun	nber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 38	ft.	ELEVATION:			
N Depth of groundwater Encountered:	ft.		ft.		ft.
	ELOW LAND S		URED ON mo/o	• •	/14
Pump test data: Well water was  Description:  Pump test data: Well water was  Est. Yield: gpm Well water was		ft. after		of pumping @	gpm
	o <b>38</b> ft	ft. after and	in.	of pumping @ to	gpm ft.
₩ELL WATER TO BE USED AS:			9 Dewateri	44 1 1	tion well
1. Domestic 3. Feedlot 5. Public water sup				12. Other (Sp	ecify below)
2. Irrigation 4. Industrial 6. Oil field water su Was a chemical/bacteriological sample submitted to Department			10. Monitoria	n <b>g well</b> what mo/day/yr w	as samnle
S Was a chemical/bacteriological sample submitted to Departme submitted		NO Water Well Disir			10
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specif	y below) CA	SING JOINTS: (	Glued	Threaded
1. Steel 3. RPM (SR)	SDR-26			Welded	Clamped
4.700	n. to	ft.,	Dia.	: <u> </u>	4
12		,		in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35	lbs. / ft.	vvaliti	hickness or gaug	ge No214	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	<b>1</b> 1. O	ther (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	0. Asbestos-Ce	ment 12. N	one used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7	. Torch cut	9. <b>Dri</b> l	lled holes	11. None ( o	pen hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	. Saw cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL From 25 ft. to 3	<b>8</b> ft.,	From	ft.	to	ft.
From ft. to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From 24 ft. to 3	<b>8</b> ft.,	From	ft.	to	ft.
From ft. to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	,	Other bent	onite hole pli	ıg
Grout intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					ft.
What is the nearest source of possible contamination:  1. Septic tank 4. Lateral lines 7. Pit privy 10. Live	stock pens	13. Insect	ticide storage	15. Oil well/G	as well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					ecify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? East		How m	any feet? 10 f	-	
From To LITHOLOGIC LOG Fro	m To		LITHOLC	GIC LOG	
0 3 topsoil 3 8 sand and clay					
8 15 fine sand					
15 28 medium sand					
28 38 grey shale					
					***
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2.	reconstructe	d or 3.	plugged	under my jurisdicti	on and
was completed on (mo/day/year)  5/21/14  and this record is true to the best of my knowledge and belief.					
· · · · · · · · · · · · · · · · · · ·					
Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  5/23/14					
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp					