	WATER WEL	L RECO	RD F	orm WV	VC-5 F	KSA 82a-	1212				
1 LOCATION OF WATER WELL:	FRACTION			SECTION NUMBER				RANGE NUMBER			
Sedgwick		NE 1/4	NE_	1/4	34	T	28 S	R	1E	E/W	
Distance and direction from nearest town or city 3009 E. Sunflower	Derby, Kansas	,	γ?								
	SEPH, Charles	•									
	E. Sunflower						Board of	Agriculture, Division	n of Wat	ler Resource	
CITY, STATE: Derb	y, Kansas			Z	P CODE:	67037	Application	Number:		_	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF CHARG	WELL:	50	ft.		ELEVATIO	N:				
	pth of groundwater En	countered:		ft			ft.			ft.	
	ELL'S STATIC WATE	R LEVEL	15	FT. BELC	W LAND S	URFACE ME	ASURED ON n	no/day/yr:	7/25/1	14	
NWNE	·	test data:	Well water			ft. after		ours of pumping	_	gpm	
₩ W E B	Est. Yield: ore Hole Diameter	gpm 12 in	Well wate	er was to 5	50 4	ft. after		ours of pumping	_	gpm	
	ELL WATER WAS SU		l.	10 2	5 U 1	t. and		44	to Injecti	ft. ion well	
	. Domestic 3. Fee		oublic water	er supply	7. Lawn	and garden	9. Dewat only	g	-	cify below)	
	-		Oil field wa		8. Air co	nditioning		oring well			
	Vas a chemical/bacteriolog bmitted	gical sample sul	bmitted to De	epartment?	YES	NO Water Well D	-	es, what mo/day	//yr wa: NC		
5 TYPE OF CASING USED:							CASING JOINTS			hreaded	
1. Steel 3. RPM (SF	₹) 5. Wrought Iron	n 7. F	iberglass	9. 0	ther (Specif	y below)	CASING JOINT	Welded		Clamped	
2. PVC 4. ABS	6. Asbestos-Ce	ement 8. C	Concrete tile	9						riapuu	
Blank casing diameter	in. to	ft.,	Dia.	in.	to	ft.,	Dia.	in. to)	ft.	
Casing height Control Surface:	in.,	We	eight:	11	bs. / ft.	Wa	III thickness or g	auge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)					BS .sbestos-Ce		. Other (specify) . None used (op				
]		0. 10	VIF (SIK)	10. A	spesios-ce	mem 12	. None used (op	en noie)			
SCREEN OR PERFORATION OPENING 1. Continuous slot 3. Mill slo		zed wranned	ı	7 To	rch cut	9.1	Drilled holes	11 No	ne (one	en hole)	
					w cut				ic (opc		
	Inched 6. Wire	wrapped		8. Sa	w cut	10. 0	Other (specify)	IN/A			
SCREEN - PERFORATION INTERVAL	From	ft.	to		ft.,	From	ft.	to)	ft.	
	From	ft.	to		ft.,	From	ft.	to	1	ft.	
GRAVEL PACK INTERVALS:	From	ft.	to		ft.,	From	ft.	to)	ft.	
	From	ft.	to		ft.,	From	ft.	to) 	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug								_			
Grout Intervals: From What is the nearest source of possible co	ft. to	ft.,	From	ft.	to	ft.,	From	2 ft.	to 22	Z ft.	
1. Septic tank 4. Lateral lines 7. Pit privy			10	10. Livestock pens 13. Insec			ecticide storag	_			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (spec							ify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage											
Direction from well? North					T -	How	many feet? 6				
From To LITHOLOGIC LOG				From	To			OGIC LO	<u>; </u>		
					22	sandy top	hole plug				
				22	50	chlorinat					
							J				
						ļ					
		· · · · · · · · · · · · · · · · · · ·				<u> </u>					
					L	l					
Contractor's or Landowner's Certific		was 1. cor	nstructed	2. red	constructe	d or 3.0	plugged	under my juri	sdiction	and	
was completed on (mo/day/year)	7/25/2014	and thi	is record is	true to the	best of my	knowledge a	nd belief.				
Kansas Water Well Contractor's Licens	e No. 236	This	water well	record wa	s completed	d on (mo/day/	year) 7/	25/2014			
under the business name of Harp Well and Pump Service by (signature) Todd S. Howb											