

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		NW ¼ NW ¼ NW ¼		1		T 28 S		R 1	
Distance and direction from nearest town or city street address of well if located within city?									
2410 S. Oliver, Wichita, Kansas									
2 WATER WELL OWNER: Conoco Inc.									
RR#, St Address, Box # P.O. Box 2197									
City, State, ZIP Code Houston, TX 77252-2192									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 22 ft ELEVATION: 1308.28							
N		Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft							
1 Mile		WELL'S STATIC WATER LEVEL 11.12 ft below land surface measured on mo/day/yr 6/10/98							
W		Pump test data: Well water was NA ft after hours pumping gpm							
E		Est Yield NA gpm: Well water was ft after hours pumping gpm							
S		Bore Hole Diameter 8 in. to 22 ft, and in. to ft							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded									
Blank casing diameter 2 in. to 10 ft, Dia in. to ft, Dia in. to ft									
Casing height above land surface 4.56 in., weight Sch 40 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 10 ft to 20 ft, From ft to ft									
From ft to ft, From ft to ft									
GRAVEL PACK INTERVALS: From 8 ft to 22 ft, From ft to ft									
From ft to ft, From ft to ft									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft to 6 ft, From 6 ft to 8 ft, From ft to ft									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? Southeast How many feet? 110									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 6 Clay, Brown									
6 10 Clay, Dark Brown									
10 15 Clay, Gray									
15 22 Shale, Green/Yellow/Red/Gray									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction									
and was completed on (mo/day/year) 6/4/98 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 6/25/98									
under the business name of GeoCore Services, Inc. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-298-5545. Send one to WATER WELL OWNER and retain one for your records.									