WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: **FRACTION** SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE 1/4 SE NE 18 1/4 1/4 Т 28 S R 1E E/W Distance and direction from nearest town or city street address of well if located within city? 4100 S. Seneca Wichita, Kansas (3 constructs on 1 permit) IRON HOUSE MFG. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 4100 S. Seneca Wichita, Kansas CITY, STATE: 20160219 ZIP CODE: Application Number: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was NW NEft. after hours of pumping @ gpm Est. Yield: gpm Well water was hours of pumping @ <u>a</u> ft. after gpm ≌ Bore Hole Diameter 12 to 35 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 9. Other (Specify below) **CASING JOINTS:** Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 8 20 in. to ft.. Dia. in to ft Dia to ft. 12 Casing height above land surface: in., Weight: 5.52 Wall thickness or gauge No. lbs. / ft. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2 Brass 8. RMP (SR) 6. Concrete Tile 4. Galvanized 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 20 From to 35 ft., From ft. to From ft. to ft.. From ft. 20 GRAVEL PACK INTERVALS: ft. 28 From ft.. From ft. ft. From ft. to ft., From to ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From O ft 20 ft From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From LITHOLOGIC LOG Τо From Τo LITHOLOGIC LOG topsoil 3 12 clay 25 12 fine sand 25 35 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 12/1/16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (moldaylyear) 12/5/16 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb