WATER WELL RECORD Form WWC-5						Division of Water						
	Original Record Correction Change in Well Use 1 LOCATION DF WATER WELD: Fraction				Resources App. No. Well ID							
1 LOCA	TIONOFV	VATER WEI	2:	Fraction	se se	ction Numb	per	Township Numb	2	nge Number		
County: Selective WIND												
Address: 643 E 3/25										_		
City: USCILLE State: 1 21P: 0/210												
3 LOCATE WELL WITH "X" IN SECTION BOY: 4 DEPTH OF COMPLETED WELL: Depth(s) Groundwater Encountered: 1)												
	'X" IN ON BOX:	Depth(s) Gr	oundwater E	ncountered: 1)	5 a .			e:				
	N 2) ft. 3) ft., or 4)						Dry Well Horizontal Datum: WGS 84 NAD 83 NAD 27					
T.		-yr) //-/5	-/6 Sour		Latitude/Longitude							
3	NE	☐ above I	and surface,	-yr)	GPS (unit make/model:							
WAL-	NE	Pump test d	ata: Well wa	ft.	☐ Land Survey ☐ Topographic Man							
w	E after hours pumping					Online Mapper:						
sw	SE	Well wa	ft.									
<u> </u>	afterhours pumpinggpm S Bore Hole Diameter:gn. in. to					6 Elev	ation	:ft.	☐ Ground	Level TOC		
	S	Bore Hole I)iameter:	2 in. to 1.3	ft. and	Source		Land Survey				
	mile			in. to	ft .			Other				
7 WELL WATER TO BE USED AS: 1. Domestic: 5. □ Public Water Supply: well ID												
1. Domestic				er Suppry: well 110 e: how many wells?								
	& Garden		charge: well ID		11. Test Hole: well ID							
☐ Livest	vestock 8. ☐ Monitoring: well ID					12. Geothermal: how many bores?						
2. Irrigat				Remediation: well I				Loop Horizonta				
3. ☐ Feedle 4. ☐ Indust			Air Sparge Recovery	☐ Soil Vapor ☐ Injection	Extraction			Loop Surface Dis				
Was a chemical/bacteriological sample submitted to KDHE? Yes Yoo If yes, date sample was submitted:												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: LaGlued Clamped Welded Threaded												
Casing diameter												
Casing height above land surface												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)												
SCREEN OR PERFORATION OPENINGS ARE:												
☐ Continuous Slot												
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)												
SCREEN-PERFORATED INTERVALS: From 30												
GRAVEL PACK INTERVALS: From												
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other												
Nearest source of possible contamination:												
Septic			Lateral Lines		_	Livestock Po		☐ Insectic				
☐ Sewer		_	Cess Pool	☐ Sewage La		Fuel Storage			ned Water V	Vell		
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well □ Other (Specify) □ Other (Specify)												
Direction fro		Dout	<i>y</i>	Distance from w	ell?6	5		ft.				
10 FROM	ТО	L L	THO LOG	IC LOG	FROM	то	LITI	HO. LOG (cont.) or	PLUGGING	INTERVALS		
5	4/ "	10%	2 200	ey Q	1							
4	20		-inc	Jan Ca		2						
20	40	60	wa.	Jan J	Janel	<u> </u>						
												
		······································										
					Notes:	· · · · · · · · · · · · · · · · · · ·						
	D (CTC-	AW V 15		(MD)	1		1					
under my in	KACTOR'S	OR LANDO	JWNER'S	CERTIFICATION orday-year)	5 - Teans	r well was [this record	XL C01	nstructed, [] recore to the best of my	istructed, c	e and belief		
Kansas Wa	ter Well Co	ntractor's Lice	ense Noo7	This W	ater Wolland	ord was co	mple	ed on (mo)day, ye	ar)	17576		
under the b	usiness nam	جبر <i>لسلا</i> . e of	استعلى المسائدة	7 present	Si	gnature)		wet 15	رکامی			
				constructed well to: Kar								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.eov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015												