A LOCATION OF WATER WEST	WATER WE	LL RECO	RD F	orm WV	C-5	KSA 82a-12		7 544	IGE NUMBER
1 LOCATION OF WATER WELL:	FRACTION NW 1/4	SW 1/4	SW		15		PNUMBER 8 S	1	1E E/W
Sedgwick Distance and direction from nearest town or city st	<u> </u>			1/4	15	T 2	0 5	] R	TE E/VV
1640 E. Fernwood	Wichita, K		ıt <b>y</b> r						
WATER WELL OWNER: ARCH		411343							
	E. Fernwood						Board of A	griculture, Divisio	on of Water Resource
	ita, Kansas			ZI	CODE:		Application N	umber:	
3 LOCATE WELL'S LOCATION 4 DI	EPTH OF PUR	GO WELL:	23	ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	th of groundwater I			ft.			ft.		ft.
	LL'S STATIC WAT	ER LEVEL	17	FT. BELO	W LAND S	SURFACE MEASI	JRED ON mo	o/day/yr:	3/31/17
NWNE	Pum	p test data:	Well water	er was		ft. after	hou	irs of pumping	@ gr
<u>⊕</u> w	Est. Yield:	gpm	Well water	er was		ft. after	hou	irs of pumping	_
	re Hole Diameter	<b>1 1/4</b> i	n.	to	f	ft, and	in.		to f
	LL WATER (1945)		Public wat	or eupphy	7 Jawn	and garden onl	9. Dewate	9	. Injection well
						enditioning	7 10. <b>Monito</b>		er (Specify belo
I I I I I I I I I I I I I I I I I I I	as a chemical/bacterio		Oil field wa ubmitted to D		YES	(NO)		_	y/yr was sample
<b>y</b> 1	mitted					Water Well Disin	fected?	YES	NO
TYPE OF CASING USED:	5. Wrought I	ron 7.	Fiberglass	9. Ot	her (Speci	fy below) CAS	SING JOINTS	Glued	Threaded
1. Steel 3. RPM (SR)	)		J	SDI	R-26			Welded	Clamped
2. PVC 4. ABS	6. Asbestos-		Concrete til	9		_			
Blank casing diameter 1 1/4 in		ft.,	Dia.	in.	to	ft.,	Dia.	in. to	o ft.
Casing height parameters can be considered as a surface:	24 in.,	W	/eight:	lb	s. / ft.	Wall th	ickness or ga	uge No.	
TYPE OF SCREEN OR PERFORATION I  1. Steel 3. Stainless Steel		7 0	PVC	9. AI	96	11 0	her (specify)		
	<ol> <li>Fiberglass</li> <li>Concrete Til</li> </ol>		RMP (SR)		sbestos-C∈		one used (ope	n hole)	
		e 0.r	(IVIF (SIC)	10. A	5065105-06	311611t 12.14	nie useu (ope	ii noie)	
SCREEN OR PERFORATION OPENINGS	-			7.7-		0 8-41	led holes	44 No.	ne ( open hole)
1. Continuous slot 3. Mill slot		auzed wrappe	ea		rch cut			II. NO	ne ( open noie)
2. Louvered shutter 4. Key pur	nched 6. W	ire wrapped		8. <b>Sa</b>	w cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL	From	ft.	to		ft.,	From	ft.	to	ft.
	From	ft.	to		ft.,	From	ft.	to	o ft.
GRAVEL PACK INTERVALS:	From	ft.	to		ft.,	From	ft.	to	o ft.
	From	ft,	to		ft.,	From	ft.	to	o ft.
GROUT MATERIALS: 1. Neat co	ement	2. Cement G	rout	3	. Bentonit	ie .	Other ber	tonite hol	e plug
Grout Intervals: From	ft. to	ft.,	From	ft.	to			<b>2</b> ft.	
What is the nearest source of possible con	7	Pit privy		). Livestoc			icide storage		vell/Gas well
1. Septic tank 4. Lateral i					•		•	40 045	er (specify belov
2. Sewer lines 5. Cess Po		Sewage lagoo		1. Fuel stor	_	14. Aband	on water we	10.00	(opcony 20.0.
3. Watertight sewer line 6. Seepage	e pit 9.	Feed yard	1.	2. Fertilizer	storage	Llav	642		
From To L	ITHOLOGIC	LOG		From	То	T How III	I ITHOL	OGIC LO	3
10	MINOLOGIO	<u> </u>		0	2	compacted		COIO LO	
				2	23	bentonie ho			
							1 0		
	· · ·					-			
					<del></del>	<del> </del>			
								•	

and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

4/6/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp