WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NWNE SE 20 1/4 1/4 1/4 Т 28 S 1**E** E/W R Distance and direction from nearest town or city street address of well if located within city? 5346 S. Stoneborough Ct. Wichita, Kansas CHANDLER, Paul WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 5346 S. Stoneborough Ct. ZIP CODE: 67217 Wichita, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPLETED WELL: 46 ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. Ν WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/29/17 Pump test data: Well water was ft. after hours of pumping @ MW-- NF gpm Est. Yield: Well water was apm ft. after hours of pumping @ gpm ≅w 12 to 46 Bore Hole Diameter and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 6. Oil field water supply 8. Air conditioning 4. Industrial Was a chemical/bacteriological sample submitted to Department? (NO) ; If yes, what mo/day/yr was sample Was Water Well Disinfected? (YES NO TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: CGlued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 Blank casing diameter 36 Dia in. to ft.. in. ft., Dia in ft. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9. ABS 11. Other (specify) 5. Fiberglass 1. Steel 2. Brass Concrete Tile 8. RMP (\$R) 4. Galvanized 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 9. Drilled holes 7. Torch cut 11. None (open hole) 2. Louvered shutter 8. Saw cut 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 36 46 From to ft., From ft. ft. to ft. From to ft., From ft. to ft 24 GRAVEL PACK INTERVALS: ft. to 46 From ft., From ft. ft. ft From to ft., From ft to ft. **GROUT MATERIALS:** Other 1. Neat cement 2 Cement Grout bentonite hole plug 3. Bentonite Grout Intervals: 4 From ft 24 ft. From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 2. Sewer lines 5. Cess Pool 14. Abandon water well 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North Direction from well? How many feet? 50 ft. plus From LITHOLOGIC LOG Τо From To LITHOLOGIC LOG 0 topsoil 3 10 clay 10 25 fine sand 25 46 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed ΟΓ 3. plugged under my jurisdiction and

was completed on (mo/day/year)

9/29/17

and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

10/4/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Horb