

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SE 1/4 SE 1/4	SECTION NUMBER 29	TOWNSHIP NUMBER T 28 S	RANGE NUMBER R 1E E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
39th & Fairview Wichita, Kansas (2 constructs on 1 permit)

2 WATER WELL OWNER: RR#, ST. ADDRESS, BOX #: CITY, STATE:	WICHITA, CITY OF 455 N. Main Wichita, Kansas	Board of Agriculture, Division of Water Resource Application Number: 20180033	ZIP CODE:
--	---	---	-----------

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION:		
---	--	--	--

Depth of groundwater Encountered: _____ ft. **2/2/18** ft.

WELL'S STATIC WATER LEVEL **11** FT. BELOW LAND SURFACE MEASURED ON _____ mo/day/yr:

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter **12** in. to **36** ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only **9. Dewatering** 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? **YES** **NO**; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? **YES** **NO**

5 TYPE OF CASING USED:	1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded		
	2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped		
Blank casing diameter	8 in.	to 20 ft., Dia.	in. to ft., Dia. in. to ft.
Casing height above land surface:	12 in.,	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)			
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)			
SCREEN - PERFORATION INTERVAL From 20 ft. to 26 ft., From ft. to ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 36 ft., From ft. to ft. to ft.			

6 GROUT MATERIALS:	1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug		
Grout intervals: From 0 ft. to 20 ft., From ft. to ft. to ft. From ft. to ft. to ft.			
What is the nearest source of possible contamination:			
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None			
Direction from well?			How many feet?

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	6	clay			
6	24	fine sand			
24	36	medium sand			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 2/2/18 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 under the business name of Harp Well and Pump Service	This water well record was completed on (mo/day/year) 2/7/18 by (signature) Todd S. Harp