| | Form WWC-5 | KSA 82a-1212 | |
|--|--|--------------------------------------|---------------------------------------|
| 1 LOCATION OF WATER WELL: FRACTION | SECTION NUMBE | | RANGE NUMBER |
| Sedgwick SE 1/4 SE 1/4 SW | 1/4 6 | T 28 S | R 1E E/W |
| Distance and direction from nearest town or city street address of well if located within city? NW corner of Glenn & 31st So. Wichita, Kansas | (11 plugs o | n ana narmit) | |
| 2 WATER WELL OWNER: WICHITA, CITY OF | (11 plugs of | n one permit) | |
| RR#,ST. ADDRESS,BOX #: 455 N. Main | | Board of Ag | riculture, Division of Water Resource |
| CITY, STATE: Wichita, Kansas | ZIP CODE: | Application Nu | mber: 20170198 |
| 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMMETARE WELL: 4 | | ELEVATION: | |
| WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered: | ft. | ft. | ft. |
| WELL'S STATIC WATER LEVEL 12 | | SURFACE MEASURED ON mo/ | |
| NW NE Pump test data: Well wa | | | rs of pumping @ gpm |
| Est. Yield: gpm Well wa | ater was | ft. after hour | rs of pumping @ gpm |
| | to f | t, and in. | to ft. |
| WELL WATER TOPES USED AS: 1. Domestic 3. Feedlot 5. Public wa | stereupply 7 lawn | and garden only 9. Dewater | 4 |
| 2. Irrigation 4. Industrial 6. Oil field w | , | onditioning 10. Monitori | 12. Other (Specify below) |
| S Was a chemical/bacteriological sample submitted to | | | what mo/day/yr was sample |
| submitted | Was | Water Well Disinfected? | YES NO |
| TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass | Other (Specif | fy below) CASING JOINTS: | Glued Threaded |
| 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete t | ile | | Welded Clamped |
| Blank casing diameter 8 in. to ft., Dia. | in. to | ft., Dia. | :- 4- 64 |
| 40 | | | in. to ft. |
| Casing height TYPE OF SCREEN OR PERFORATION MATERIAL: Weight: | lbs. / ft. | Wall thickness or gau | ige No. |
| 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC | 9. ABS | 11. Other (specify) | N/A |
| 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) | 10. Asbestos-Ce | ement 12. None used (oper | n hole) |
| SCREEN OR PERFORATION OPENINGS ARE: | | | |
| 1. Continuous slot 3. Mill slot 5. Gauzed wrapped | 7. Torch cut | 9. Drilled holes | 11. None (open hole) |
| 2. Louvered shutter 4. Key punched 6. Wire wrapped | 8. Saw cut | 10. Other (specify) N | J/A |
| SCREEN - PERFORATION INTERVAL From ft. to | . 4 | From ft | |
| From ft. to | 127, | _ | to ft. |
| GRAVEL PACK INTERVALS: From ft. to | , | From ft. From ft. | to ft. |
| From ft. to | 14., | _ | to ft. |
| C CROUT MATERIALS: | | | to ft. |
| Grout Intervals: From ft. to ft., From | 3. Bentonit | C Bell | tonite hole plug |
| What is the nearest source of possible contamination: | ft. to | , | |
| | 10. Livestock pens | 13. Insecticide storage | 15. Oil well/Gas well |
| 2. Sewer lines 5. Cess Pool 8. Sewage lagoon | 11. Fuel storage | 14. Abandon water well | 16. Other (specify below) |
| | 12. Fertilizer storage | | |
| Direction from well? From To LITHOLOGIC LOG | T F T | How many feet? | 2010100 |
| From To LITHOLOGIC LOG | From To | | OGIC LOG |
| | 0 4 24 | compacted clay bentonit hole plug | |
| | 24 45 | chlorinated gravel | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | 100 |
| | | | |
| | | | |
| Contractor's or Landowner's Certification: This water well was 1. constructed | f 2. reconstructe | ed or 3. plugged | under my jurisdiction and |
| was completed on (mo/day/year) 3/27/18 and this record is true to the best of my knowledge and belief. | | | |
| Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/29/18 | | | |
| under the business name of Harp Well and Pump Service by (signature) Todd S. Harb | | | |
| Traip wen and I unip Service | -, (0.30.0.0) | i ouw s | . $\pi\omega p$ |