

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.


Well ID

Well ID

1 LOCATION OF WATER WELL: County: Sedgwick Fraction nw 1/4 ne 1/4 sw 1/4 ne 1/4 Section Number 12 Township Number T 28 S Range Number R 1 E W

2 WELL OWNER: Last Name: Business: McConnell AFB Address: 57830 Pittsburg ST Suite 120 City: McConnell AFB State: KS ZIP: 67221 Street or Rural Address where well is located

3 LOCATE WELL WITH 'X' IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 41 ft. Depth(s) Groundwater Encountered: 1) n/a ft. 2) ft. 3) ft. or 4) Dry Well

5 Latitude: 37.6323167 (decimal degrees) Longitude: -97.2695806 (decimal degrees) Horizontal Datum: WGS 84 NAD 83 NAD 27

6 Elevation: N/A ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID 3. Dewatering: how many wells? 4. Aquifer Recharge: well ID 5. Monitoring: well ID 6. Environmental Remediation: well ID 7. Air Sparge 8. Soil Vapor Extraction 9. Recovery 10. Injection 11. Oil Field Water Supply: lease 12. Test Hole: well ID 13. Geothermal: how many bores? 14. Closed Loop 15. Horizontal 16. Vertical 17. Open Loop 18. Surface Discharge 19. Inj. of Water 20. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 2 in. to 33 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 0 in. Weight 68 lbs./ft. Wall thickness or gauge No. SCH #40

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Brass Galvanized Steel Concrete tile None used (open hole) Other (Specify)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 41 ft. to 25 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 25 ft. to 0 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) n/a Direction from well? n/a Distance from well? ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Row 1: 0' TO 1', Brown Clay. Row 2: 1' TO 41',

Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed or plugged under my jurisdiction and was completed on (mo-day-year) 05-18-2018 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 567. This Water Well Record was completed on (mo-day-year) 05-14-2018 under the business name of Cascade Drilling LP. Signature