		WATER V	VELL R	ECORD	For	m WW	/C-5 K	SA 82a-12	212			
1 LOCATION OF WATER	R WELL:	FRACTION			a.		ION NUMBER	i	IIP NUMBER	RANGE NUMBER		
Sedgwick		NW 1/4			SE 1	/4	21	<u> </u>	28 S	R	1E	E/W
Distance and direction from 1303 E. Mayw		street address of w Wichita, Ka		within city?								
2 WATER WELL O	Y 0711	E, MIKE C		UCTION	V							
RR#,ST. ADDRESS,									Board of Ag	griculture, Divisio	n of Wate	er Resource
CITY, S		y Center, K			- 4	ZII	P CODE: 6		Application Nu	ımber:		
3 LOCATE WELL'S LO WITH AN "X" IN SEC	CATION 4	EPTH OF COM	IPLETED V	NELL:	36	ft.		ELEVATION:				
N N	Dep	th of groundwat			•	ft.			ft.		(11311	ft.
	1 1	LL'S STATIC W			-		W LAND SU	JRFACE MEAS ft. after	SURED ON mo	/day/yr: rs of pumping	6/1 <b>2</b> /1	. <b>o</b> gpm
NW NW	-NE	Est. Yield:	ump test d gpm		ell water ell water			ft, after		rs of pumping	_	gpm
w Mile	E Bo	re Hole Diamet	· · · · ·	<b>2</b> in.		to 3	6 ft.	and	in.		to	ft.
-		LL WATER TO		AS:		_			9. Dewater	ring <sup>11.</sup>	Injection	on well
」 │ sw 📐		-	3. Feedlot					ind garden on	سوا 10. Monitor		er (Spec	cify below
		Irrigation as a chemical/bac	<ol> <li>Industrial teriological sa</li> </ol>			er supply artment?	YES	NO		, what mo/day	/yr was	sample
<u> </u>		mitted						Vater Well Disi	nfected?	YES	NO	l 
5 TYPE OF CAS		5. Wroug	ht Iron	7. Fiber	glass	9. Of	ther (Specify	below) CA	SING JOINTS:		Т	hreaded
1. Steel	3. RPM (SR > 4. ABS	•	os-Cement	t 8. Cond	rete tile	SDI	R-26			Welded	C	Clamped
Blank casing diamete	_	in. to	26 ff	t., Di	a.	in.	to	ft.,	Dia.	in. to	)	ft.
Casing height above	land surface:	12 in.,		Weigh	ıt: <b>2.</b>	3 <b>5</b> It	os. / ft.	Wall	thickness or gai	uge No.	214	
TYPE OF SCREEN C									J-	•		
1. Steel 3	. Stainless Steel	5. Fiberglas	ss (	7. PVC	>	9. A	BS		Other (specify)			
2. Brass 4	. Galvanized	6. Concrete	Tile	8. RMP	(SR)	10. A	sbestos-Cer	ment 12. N	lone used (ope	n hole)		
SCREEN OR PERFO				_				0.5		44 No.		! ! - \
1. Continuous slot			. Gauzed v				rch cut		illed holes	11. NOI	пе ( оре	en hole)
2. Louvered shutte	r 4. Key pu	inched 6	. Wire wra	pped		8. <b>Sa</b>	w cut	10. Ot	her (specify)			
SCREEN - PERFORA	TION INTERVAL	From	26	ft.	to	36	ft.,	From	ft.	to	)	ft.
_	_	From	2.4	ft.	to	2.	ft.,	From	ft.	to	)	ft.
GRAVEL PAG	CK INTERVALS:	From	24	ft.	to	36	ft.,	From	ft.	to	)	ft.
T		From		ft.	to		ft.,	From	ft.	to		ft.
GROUT MATERI	i. Neat C			ment Grout			B. Bentonite			tonite hole		
Grout Intervals: What is the nearest so		ft. to ntamination:	o <b>24</b>	ft., F	rom	ft.	to	ft.,	From	ft.	to	ft.
1. Septic tank	4. Lateral	lines	7. <b>Pit privy</b> 10.			. Livestock pens		13. <b>Inse</b> d	13. Insecticide storage		15. Oil well/Gas well  16. Other (specify below)	
2. Sewer lines	5. Cess P	ool	8. Sewage	e lagoon	11.	Fuel sto	rage	14. Aban	don water wel	16. Otne	er (spec	ity below)
Watertight sewe		ge pit	9. Feed ya	ard	12.	Fertilize	r storage		10	64l		
From To	East	ITHOLOG	IC I OG			From	То	How r	nany feet? 10	OGIC LO	<u></u>	
0 3	topsoil	ITTIOLOG	ic Log			1 10111	10		LITTOL	OGIC LO	<u> </u>	<del></del>
	fine sand											
25 36	medium sand			***								
		T-1-1				•	-					
									•			
		-										
	ļ											
							-					
							<u> </u>					
7 Contractor's or L	andowner's Certific	ation: This wat	er well was	1. consti	ructed	2. re	constructed	1 or 3.	plugged	under my jur	isdiction	n and
was completed on		6/12/18						knowledge and		• •		
·	` ' '						•	on (mo/day/ye	-	14/18		
,	Contractor's Licens		C		17011		gnature)		odd		سان.	
I under the business	name of Harp	wen and Pl	amp ser	vice		Dy (31	3.10.010)	ı	CTLAXXI.	$\mathbf{x} = \mathbf{\pi} (\lambda)$	w I)	