WATER WELL RECORD Form WWC-5 KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER	
Sedgwick SW 1/4 SW 1/4 NW 1/4 20 T 28 S R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city?	
1018 W. Sunrise Wichita, Kansas	
2 WATER WELL OWNER: GREENE, Charles Board of Agriculture, Division of Water Resources	rce
RR#,ST. ADDRESS,BOX #: 1018 W. Sunrise Decide of Agriculate, Deficition Number: CITY, STATE: Wichita, Kansas ZIP CODE: 67217 Application Number:	
N Depth of groundwater Encountered: ft. π. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/23/19	
	gpm
	ipm
	ft.
well watering 11 injection well	
12. Other (Specify below 12. Other (Specify be	ow)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well S Vas a chemical/bacteriological sample submitted to Department? YES NO 11 yes, what mo/day/yr was sample	e
s Was a chemical/bacteriological sample submitted to Department? YES NO , if yes, what includy ye was completed was water Well Disinfected? YES NO	
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded	t
1. Steel 3. RPM (SR) Visiting Competence SDP 26 Welded Clamped	1
2. PVC 4. ABS 6. Aspestos-Cement 6. Concrete tile	
Blank casing diameter 5 in. to 30 ft., Dia. in. to ft., Dia. in. to ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	、
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)	,
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 30 ft. to 40 ft., From ft. to ft.	
From ft. to ft., From ft. to ft	
GRAVEL PACK INTERVALS: From 24 ft. to 40 ft., From ft. to ft.	
From ft. to ft., From ft. to ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug	
Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well	
1. Septic tank 7. Lateral mes	w)
2. Sewer lines 5. Cess Pool 6. Contage lageon 74. Abandon water wen	•
③ Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 30 ft. plus	
From To LITHOLOGIC LOG From To LITHOLOGIC LOG	
3 22 fine sand	
22 40 medium sand	
	<u></u>
<u>↓</u>	
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and	
was completed on (mo/day/year) 5/23/19 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/27/19	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp	