	WATER	WELL RECOR	D Form	WWC-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL:	FRACTION			SECTION NUMBE	1	IP NUMBER	RANGE N	
Sedgwick		1/4 NW 1/4	SW 1/4	32	T 2	.8 s	R 1	E E/W
Distance and direction from nearest to 307 E. Karla.	•	•	?					
2 WATER WELL OWNER:	Wichita, ARMSTRONG							
RR#,ST. ADDRESS,BOX #:	7540 W. North					Board of Agr	iculture, Division of	Water Resource
CITY, STATE:	Wichita, Kansa	ıs		ZIP CODE: 6	7205	Application Nur	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX	4 DEPTH OF CO	OMPLETED WELL:	46	ft.	ELEVATION:			
WITH AN "X" IN SECTION BOX	Depth of groundw	vater Encountered:		ft.		ft.		ft.
1	WELL'S STATIC			BELOW LAND SU				7/19
	F-4 V:-14.		Well water was		ft. after ft. after		s of pumping @ s of pumping @	gpm gpm
W Wije	Est. Yield: E Bore Hole Diam	4.0	Well water was	to 46 ft		in.	to	ft.
- X		O BE USED AS:				9 Dewateri	44 1	ection well
sw se	1. Domestic	3. Feedlot 5. Pt	ublic water su	pply 7. Lawn :		\triangleright	12. Other (S	pecify below)
	2. Irrigation	4. Industrial 6. O i	il field water s		nditioning	10. Monitoria	ng well what mo/day/yr	was sample
S	submitted	actenological sample subi	mitted to Departin		NO Water Well Disir		YES	NO
5 TYPE OF CASING USE	5 Wro	ught Iron 7. Fit	perglass	9. Other (Specify	/ below) CA	SING JOINTS:	Glued	Threaded
1. Steel 3.	RPM (SR)		oncrete tile	SDR-26	•		Welded	Clamped
	700					D'-		
Blank casing diameter	5 in. to	,	Dia.	in. to	ft.,		in. to	ft.
Casing height above land surface TYPE OF SCREEN OR PERFO		., Wei	ight: 2.35	lbs. / ft.	Wall t	hickness or gau	ge No214	,
1. Steel 3. Stainles		ass 7. PV	$\overline{\circ}$	9. ABS	11. 0	ther (specify)		
2. Brass 4. Galvaniz	zed 6. Concre	ete Tile 8. RM	IP (SR)	10. Asbestos-Ce	ment 12. N	one used (open	hole)	
SCREEN OR PERFORATION	OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped		7. Torch cut	9. Dri	lled holes	11. None (open hole)
2. Louvered shutter	4. Key punched	6. Wire wrapped		8. Saw cut	10. Oth	ner (specify)		
SCREEN - PERFORATION INT	ERVAL From	30 ft.	to 4	16 ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTER	RVALS: From	24 ft.	to 4	16 ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft,	to	ft.
6 GROUT MATERIALS:	1. Neat cement	2. Cement Gro	out	3. Bentonite	}	Other bent	onite hole pl	ug
Grout Intervals: From	4 ft.	to 24 ft.,	From	ft. to	ft.,	From	ft. to	-
What is the nearest source of po	ossible contamination: 4. Lateral lines	7. Pit privy	10. Liv	estock pens	13. Insect	ticide storage	15. Oil well/	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon				el storage		14. Abandon water well 16. Other (specify below)		
	6. Seepage pit	9. Feed yard	12. Fe r	tilizer storage				
Direction from well? Nor					How m	any feet? 50	ft. plus	
From To	LITHOLO	GIC LOG	Fr	om To		LITHOLO	GIC LOG	
0 3 topsoil						· · · · · · · · · · · · · · · · · · ·		
3 11 clay 11 29 fine sa	nd						· · ·	
	m sand							
7 Contractor's or Landowne		_	structed 2	. reconstructe	d or 3.	plugged	under my jurisdic	tion and
was completed on (mo/day/y	ear) 5/17/1	9 and this	s record is true	to the best of my	knowledge and	belief.		
Kansas Water Well Contracto	or's License No. 236	This	water well reco	rd was completed	d on (mo/day/ye	ar) 5/2	0/19	
under the business name of	Harp Well and l	Pump Service		by (signature)	au	odd S	Hart)