WATE	R WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION		SECTION NUMBER		RANGE NUMBER
Sedgwick NW	1/4 SE 1/4 SE	1/4 21	T 28 S	R 1E EW
Distance and direction from nearest town or city street address 5419 S. Victoria Wichita, K	•			
2 WATER WELL OWNER: RICHARDSO				
RR#,ST. ADDRESS,BOX #: 5419 S. Victor				riculture, Division of Water Resource
CITY, STATE: Wichita, Kan		ZIP CODE: 6	7216 Application Nu	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF	COMPLETED WELL: 3	5 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of ground	dwater Encountered:	ft.	ft.	ft.
WELL'S STAT	IC WATER LEVEL 15	FT. BELOW LAND SU	IRFACE MEASURED ON mo/	day/yr: 10/21/20
NWNE	Pump test data: Well wa			s of pumping @ gpm
Est. Yield:	1.0	ter was to 35 ft.	•	rs of pumping @ gpm to ft.
	TO BE USED AS:	-	Q Dewater	44 Intertien well
1. Domestic	3. Feedlot 5. Public wa	ter supply 7. Lawn a	and garden only	12. Other (Specify below)
2. Irrigation	4. Industrial 6. Oil field w	att. capp.,	nditioning 10. Monitor	ing well what mo/day/yr was sample
S Was a chemical submitted	l/bacteriological sample submitted to I		NO ; if yes, Vater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5 W	ought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR) Welded Clamped				
2. FVC 4. ABO			# Dia	:
		in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cernent 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From	, 26 ft. to	36 ft.,	From ft.	to ft.
From	ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From	24 ft. to	o 36 ft.,	From ft.	to ft.
From	ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3. Bentonite	Other ben	tonite hole plug
Grout Intervals: From ft.	to ft., From	ft. to	ft., From	1 ft. to 24 ft.
What is the nearest source of possible contamination 1. Septic tank 4. Lateral lines		10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? West			How many feet? 20	
	OGIC LOG	From To	LITHOLO	OGIC LOG
0 3 topsoil 3 12 clay				
12 25 fine sand				
25 36 medium sand				
		<u> </u>		
		 		
	· · · · · · · · · · · · · · · · · · ·			
				<u> </u>
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and				
was completed on (mo/day/year) 10/21/2020 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/23/2020				
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb				