

WELL #6		WATER WELL RECORD		Form WWC-5	KSA 82a-1212
LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 SE 1/4 NE 1/4	1	T 28 S	R 1
Distance and direction from nearest town or city street address of well if located within city?					
5800 E. Pawnee, Wichita, Kansas					
WATER WELL OWNER: Cessna Aircraft Co.					
RR#, St. Address, Box #: P. O. Box 1521					
City, State, ZIP Code: Wichita, KS 67201					
Board of Agriculture, Division of Water Resources					
Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.9 ft. ELEVATION: 1328.67			
NWNE SWSE IX		Depth(s) Groundwater Encountered 1. 13.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 13.0 ft. below land surface measured on mo/day/yr 10/18/84			
		Pump test data: Well water was n/a ft. after hours pumping gpm			
		Est. Yield n/a gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8.0 in. to 25.1 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded X					
Blank casing diameter 4.0 in. to 14.0 ft. Dia 4.0 in. to 24.9 ft. Dia in. to ft.					
Casing height above land surface 29.28 in. weight lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 14.0 ft. to 19.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 11.0 ft. to 25.1 ft. From ft. to ft.					
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1.0 ft. to 11.0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Landfill					
Direction from well? North		How many feet? 50			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0.0	4.5	Dark Brown, Olive Brown, Olive Gray Silty Clay, Trace Sand and Calcareous Material			
4.5	25.1	Olive Gray and Olive Brown Highly Weathered Shale			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/18/84 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11/3/84					
Under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					