

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SE 1/4 Section Number 1 Township Number T 28 S Range Number R 1
County: Sedgwick Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: McConnell AFB
RR#, St. Address, Box #: Wichita, Kansas
City, State, ZIP Code: Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 35.0 ft. ELEVATION: 11/13/89
Depth(s) Groundwater Encountered: 1. 13.0 ft. 2. 3.0 ft. 3. 0.0 ft.
WELL'S STATIC WATER LEVEL: 11.43 ft. below land surface measured on mo/day/yr 11/13/89
Pump test data: Well water was ft. after hours pumping
Est. Yield gpm: Well water was ft. after hours pumping
Bore Hole Diameter: 1.1 in. to 35.0 ft., and in. to
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded
Blank casing diameter: 2 in. to 15.0 ft., Dia. in. to ft., Dia. in. to
Casing height above land surface: 2.2 in., weight lbs./ft. Wall thickness or gauge No. 5.4.0
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 15.0 ft. to 34.0 ft., From ft. to ft. to
GRAVEL PACK INTERVALS: From 10.0 ft. to 35.0 ft., From ft. to ft. to

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite Grout
Grout intervals: From 0.0 ft. to 7.9 ft., From 7.9 ft. to 10.0 ft., From ft. to ft. to
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) none

Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 6.0 Soil - Bu CL Dry
6.0 9.5 Clay - Tan Si Dry
9.5 24.0 " " Dark P
24.0 35.0 " " Saturated
RECEIVED JUN 15 1989 RECEIVED OCT 27 1989
MAR 05 1990 DIVISION OF ENVIRONMENT DIVISION OF ENVIRONMENT

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/13/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 494 This Water Well Record was completed on (mo/day/yr) 11/13/89 under the business name of Southwestern Lab Inc by (signature) Robert S. Sneed