

Well No. MBOW 1 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1. LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NE 1/4 NW 1/4 SE 1/4	1	T 28 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: McConnell AFB

RR#, St. Address, Box # :
City, State, ZIP Code : Wichita, KANSAS

Board of Agriculture, Division of Water Res
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 39.5 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 13.0 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 12.75 ft. below land surface measured on mo/day/yr 11/15/88

Pump test data: Well water was ft. after hours pumping

Est. Yield gpm: Well water was ft. after hours pumping

Bore Hole Diameter 11 in. to 39.5 ft., and in. to

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample wa. mitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 2 in. to 19.5 ft., Dia in. to ft., Dia in. to

Casing height above land surface -0.3 in., weight lbs./ft. Wall thickness or gauge No. 4.0

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 19.5 ft. to 39.5 ft., From ft. to ft. to

GRAVEL PACK INTERVALS: From 14.0 ft. to 39.5 ft., From ft. to ft. to

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite Grout

Grout Intervals: From 2.0 ft. to 14.8 ft., From 14.8 ft. to 14.0 ft., From ft. to ft. to

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	9.0	Fill - Br Cl			
9.0	14.0	Clay - TAN Dry			
14.0	23.0	" - " Si Damp			
23.0	32.0	" - " " "			
32.0	35.0	" - " " Saturated			
35.0	39.5	" - " " Damp			

RECEIVED OCT 27 1989

RECEIVED JUN 15 1989

RECEIVED MAR 05 1990

DIVISION OF ENVIRONMENT

DIVISION OF ENVIRONMENT

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/10/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 494 This Water Well Record was completed on (mo/day/yr) 11/30/88 under the business name of Southwestern Lab Inc by (signature) Robert S. Smead

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.