


1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NW 1/4 NW 1/4	Section Number 3	Township Number T 28 S	Range Number R 1 EW																																													
Distance and direction from nearest town or city street address of well if located within city? 2002 E. Pawnee, Wichita, Ks.																																																		
2 WATER WELL OWNER: Total Petroleum Corp. RR#, St. Address, Box #: P.O. Box 500 City, State, ZIP Code: Denver, Co. 70201 Board of Agriculture, Division of Water Resources Application Number:																																																		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 20'6" ft. ELEVATION: Depth(s) Groundwater Encountered 1. 16' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15' 10" ft. below land surface measured on mo/day/yr 3-16-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/2" in. to 20'6" ft., and in. to ft. WELL WATER TO BE USED AS: <table style="width:100%;"> <tr> <td>1 Domestic</td> <td>3 Feedlot</td> <td>6 Oil field water supply</td> <td>9 Dewatering</td> <td>12 Other (Specify below)</td> </tr> <tr> <td>2 Irrigation</td> <td>4 Industrial</td> <td>7 Lawn and garden only</td> <td>10 Monitoring well</td> <td></td> </tr> </table> Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☒				1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)	2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well																																				
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)																																														
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well																																															
5 TYPE OF BLANK CASING USED: <table style="width:100%;"> <tr> <td>1 Steel</td> <td>3 RMP (SR)</td> <td>5 Wrought iron</td> <td>8 Concrete tile</td> <td>CASING JOINTS: Glued ☐ Clamped ☐</td> </tr> <tr> <td>2 PVC</td> <td>4 ABS</td> <td>6 Asbestos-Cement</td> <td>9 Other (specify below)</td> <td>Welded ☐</td> </tr> <tr> <td></td> <td></td> <td>7 Fiberglass</td> <td></td> <td>Threaded ☒</td> </tr> </table> Blank casing diameter 2.375 in. to 10' ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Full Mount in., weight lbs./ft. Wall thickness or gauge No. Sdr 13 TYPE OF SCREEN OR PERFORATION MATERIAL: <table style="width:100%;"> <tr> <td>1 Steel</td> <td>3 Stainless steel</td> <td>5 Fiberglass</td> <td>7 PVC</td> <td>10 Asbestos-cement Sch 40</td> </tr> <tr> <td>2 Brass</td> <td>4 Galvanized steel</td> <td>6 Concrete tile</td> <td>8 RMP (SR)</td> <td>11 Other (specify)</td> </tr> <tr> <td></td> <td></td> <td></td> <td>9 ABS</td> <td>12 None used (open hole)</td> </tr> </table> SCREEN OR PERFORATION OPENINGS ARE: <table style="width:100%;"> <tr> <td>1 Continuous slot</td> <td>3 Mill slot</td> <td>5 Gauzed wrapped</td> <td>8 Saw cut</td> <td>11 None (open hole)</td> </tr> <tr> <td>2 Louvered shutter</td> <td>4 Key punched</td> <td>6 Wire wrapped</td> <td>9 Drilled holes</td> <td></td> </tr> <tr> <td></td> <td></td> <td>7 Torch cut</td> <td>10 Other (specify)</td> <td></td> </tr> </table> SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20'6" ft. to 8' ft., From ft. to ft., From ft. to ft.						1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☐ Clamped ☐	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded ☐			7 Fiberglass		Threaded ☒	1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement Sch 40	2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)				9 ABS	12 None used (open hole)	1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes				7 Torch cut	10 Other (specify)	
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☐ Clamped ☐																																														
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded ☐																																														
		7 Fiberglass		Threaded ☒																																														
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement Sch 40																																														
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)																																														
			9 ABS	12 None used (open hole)																																														
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)																																														
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes																																															
		7 Torch cut	10 Other (specify)																																															
6 GROUT MATERIAL: Grout Intervals: From 8' ft. to 4'8" ft., From 4'8" ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: <table style="width:100%;"> <tr> <td>1 Septic tank</td> <td>4 Lateral lines</td> <td>7 Pit privy</td> <td>11 Fuel storage</td> <td>14 Abandoned water well</td> </tr> <tr> <td>2 Sewer lines</td> <td>5 Cess pool</td> <td>8 Sewage lagoon</td> <td>12 Fertilizer storage</td> <td>15 Oil well/Gas well</td> </tr> <tr> <td>3 Watertight sewer lines</td> <td>6 Seepage pit</td> <td>9 Feedyard</td> <td>13 Insecticide storage</td> <td>16 Other (specify below)</td> </tr> </table> Direction from well? North How many feet? 250'						1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well	2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)																														
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well																																														
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well																																														
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)																																														
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>.75</td> <td>Asphalt</td> <td></td> <td></td> <td></td> </tr> <tr> <td>.75</td> <td>8</td> <td>Med. tannish brn to grayish tan silty clay, iron oxide staining, firm, friable, no odor.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td>10</td> <td>Sandy clay, tannish brn sandy clay, moist, no odor, iron oxides.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>15.25</td> <td>Fine-coarse grained sand, dry, no odor.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15.25</td> <td>18</td> <td>Dk gray sand, strong odor, wet, fine-coarse sand.</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18</td> <td>20'6"</td> <td>Tan sand, wet, fine-coarse grained.</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	.75	Asphalt				.75	8	Med. tannish brn to grayish tan silty clay, iron oxide staining, firm, friable, no odor.				8	10	Sandy clay, tannish brn sandy clay, moist, no odor, iron oxides.				10	15.25	Fine-coarse grained sand, dry, no odor.				15.25	18	Dk gray sand, strong odor, wet, fine-coarse sand.				18	20'6"	Tan sand, wet, fine-coarse grained.						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																													
0	.75	Asphalt																																																
.75	8	Med. tannish brn to grayish tan silty clay, iron oxide staining, firm, friable, no odor.																																																
8	10	Sandy clay, tannish brn sandy clay, moist, no odor, iron oxides.																																																
10	15.25	Fine-coarse grained sand, dry, no odor.																																																
15.25	18	Dk gray sand, strong odor, wet, fine-coarse sand.																																																
18	20'6"	Tan sand, wet, fine-coarse grained.																																																
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-16-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 3-26-94 under the business name of JB Environmental Drilling by (signature) James Bieber																																																		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																		

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4