

1 LOCATION OF WATER WELL: County: Sedgewick		FRACTION NE 1/4 NE 1/4 NE 1/4		Section Number 3	Township Number T 28 S	Range Number R 1	EW
Distance and direction from nearest town or city street address of well if located within city? 2417 South Hillside							
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Quik Trip 901 N. Mingo Tulsa, OK 74116		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.8 ft. ELEVATION: 1293.24					
		Depth(s) Groundwater Encountered 1. 18.61 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18.61 ft. below land surface measured on mo/day/yr 3/30/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS		7 Fiberglass Threaded					
Blank casing diameter in. to 9.8 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 9.8 ft. to 24.8 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 8.0 ft. to 24.8 ft., From ft. to ft.		From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 7.0 ft. to 7.0 ft., From ft. to ft., From 7.0 ft. to 8.0 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? Southwest How many feet? 40					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 14.0 Brown Clay							
14.0 17.0 Light Brown silty clay							
17.0 25.0 Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/30/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 549 This Water Well Record was completed on (mo/day/yr) 4/10/92 under the business name of J & R Drilling Services, Inc. by (signature) Ray Coors							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							