

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 NE 1/4 NE 1/4	3	T 28 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city?					
3118 E PAWNEE					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
3118 E PAWNEE					
City, State, ZIP Code :					
WICHITA KS 67211					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 24.5 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded			
Blank casing diameter 2 in. to 19.5 ft. Dia		in. to ft. Dia			
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched					
SCREEN-PERFORATED INTERVALS:		From 14.5 ft. to 24.5 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 8.5 ft. to 24.5 ft. From ft. to ft.			
6 GROUT MATERIAL:		3 Bentonite 4 Other			
1 Neat cement 2 Cement grout					
Grout Intervals: From 0 ft. to 8.5 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? SW NE		How many feet? 500'			
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	14	CLAY			
14	TO	SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/2/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 162 W This Water Well Record was completed on (mo/day/yr) 2/3/93 under the business name of LAYNE by (signature) <i>[Signature]</i>					