

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction N E ¼ N E ¼ NE ¼	Section Number 3	Township Number T 8 S	Range Number R 1 E W
Distance and direction from nearest town or city street address of well if located within city? 3118 E. Pawnee MW3 [Redacted]					
2 WATER WELL OWNER: Bob & Marv's Apco RR#, St. Address, Box #: 3118 E. Pawnee City, State, ZIP Code: Nichols KS 67211 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 24.5 ft.			
A map of a one-quarter section grid divided into four smaller squares labeled NW, NE, SW, and SE. A large 'X' is drawn over the NE square. To the left of the grid are vertical labels 'N' at the top and 'S' at the bottom. To the right are horizontal labels 'W' on the left and 'E' on the right.		Depth(s) Groundwater Encounteredft. ELEVATION:ft. WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr Pump test data: Well water wasft. after hours pumping gpm Est. Yield gpm Well water wasft. after hours pumping gpm Bore Hole Diameter 8 in. to 24.5 ft., andin. toft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes.....No.....			
5 TYPE OF BLANK CASING USED:					
1 Steel <u>2 PVC</u> Blank casing diameterin. toft., Diain. toft., Diain. toft. Casing height above land surfacein., weightlbs./ft. Wall thickness or gauge No.		3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued.....Clamped..... Welded..... Threaded.....			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter SCREEN-PERFORATED INTERVALS: Fromft. toft., Fromft. toft., Fromft. toft., Fromft. toft.		3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut GRAVEL PACK INTERVALS: Fromft. toft., Fromft. toft., Fromft. toft., Fromft. toft.			
		7 PVC 10 Asbestos-cement 11 Other (specify), 12 None used (open hole), 8 Saw cut, 11 None (open hole), 9 Drilled holes, 10 Other (specify)			
6 GROUT MATERIAL:					
1 Neat cement Grout Intervals: Fromft. toft., Fromft. toft., Fromft. toft., Fromft. toft.		2 Cement grout 3 Bentonite 4 Other What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? NNE How many feet? 500'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLOGGING INTERVALS
0	14	clay			
14	TD	sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/2/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 W . This Water Well Record was completed on (mo/day/yr) 2/2/93 by signature [Signature] .					