

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NE 1/4 NE 1/4 SE 1/4	4	T 28 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

NW corner of Industrial Street and Hydraulic Street

2 WATER WELL OWNER:	AAA Pawn & Loan	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	2855 Hydraulic	Application Number:
City, State, ZIP Code :	Wichita, Ks.	NA

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION: 12-27-93 ft.
	Depth(s) Groundwater Encountered 1.14 ft. 2. 13.33 ft. 3. 12-27-93 ft.
	WELL'S STATIC WATER LEVEL 13.33 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was 7.5/8 in. to 18 ft. after 18 hours pumping 10 gpm
	Est. Yield 7.5/8 gpm: Well water was 18 ft. after 18 hours pumping 10 gpm
	Bore Hole Diameter 7.5/8 in. to 18 ft. and 18 in. to 18 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted X	
Water Well Disinfected? Yes X No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 2 in. to 8 ft. Dia			11 Other (specify)
Casing height above land surface 0 in. weight 0 lbs./ft. Wall thickness or gauge No. sch. 40			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft. From 8 ft. to 18 ft.			
GRAVEL PACK INTERVALS: From 6.5 ft. to 18 ft. From 6.5 ft. to 18 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 4.5 ft. From 4.5 ft. to 6.5 ft. From 6.5 ft. to 110 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? southeast How many feet? 110				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3"	concrete			
3"	1'	fill snd, f-med grnd, yell-brn colored			
1	5	cl, v dk brn, v slty, tr v f snd, mod plst			
5	10	cl, v slty, tr v f snd, lt-med gry, mott w/oxid mat			
10	12	snd, v f-med grnd, well srted, v slty, sl clyey, yell-brn			
12	13	snd, v f-med grnd, well srted, v slty, sl clyey lt gry			
13	18	snd, f-c grnd, sl-mod grvl, rnd-subang, yell-brn in color			
					AMW4-flush mount cover

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-21-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 01-20-94 under the business name of GeoCore Services, Inc. by (signature) Don Roll
