

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE ¼ NE ¼ NE ¼	4	T 28 S	R 1 EAW
Distance and direction from nearest town or city street address of well if located within city? 1535 E. Pawnee; Wichita, KS 40865090 MW-4					
WATER WELL OWNER: FINA Oil and Chemical Company RR#, St. Address, Box # : 8350 N. Central Expressway City, State, ZIP Code : Dallas, TX 75206 Board of Agriculture, Division of Water Resources Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		DEPTH OF COMPLETED WELL... 22 ft. ELEVATION: Approx. Ground Surface 1285 Depth(s) Groundwater Encountered 1. 15 ft. 2. .ft. 3. .ft. WELL'S STATIC WATER LEVEL 15.5 ft. below land surface measured on mo/day/yr 12/31/86 Pump test data: Well water was .ft. after . hours pumping gpm Est. Yield N/A gpm: Well water was .ft. after . hours pumping gpm Bore Hole Diameter 6.5 in. to 22 .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ⑩ Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X; If yes, mo/day/yr sample was submitted			
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) ② PVC 4 ABS Blank casing diameter .2 in. to 12 ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface .4 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40		CASING JOINTS: Glued . Clamped . Welded . Threaded . X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Drilled holes 12 None used (open hole)		GRAVEL PACK INTERVALS: From 12 ft. to 22 ft., From .ft. to .ft. From .ft. to .ft., From .ft. to .ft. FROM 8 ft. to 22 ft., FROM .ft. to .ft. FROM .ft. to .ft., FROM .ft. to .ft.			
GROUT MATERIAL: 1 Neat cement ② Cement grout ③ Bentonite 4 Other Grout Intervals: From 0 ft. to 2 ft., From 6 ft. to 8 ft., From .ft. to .ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy ⑪ Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? Southwest How many feet? 100			
LITHOLOGIC LOG		LITHOLOGIC LOG			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0'	4'	Dark Gray Sandy Clay			
4'	14'	Brown Silty Clay			
14'	17'	Gray-Brown Fine to Medium Sand With Clay Seams			
17'	22'	Gray-Brown Fine to Coarse Sand, Trace Gravel			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/4/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-6-87 under the business name of Terracon Consultants, Inc by signature [Signature] INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					