			WATE	R WELL RECORD	Form WWC-5	KSA 82a	n-1212		
1 LOCATIO		TER WELL:	Fraction		Sec	tion Number	Township Num	ber	Range Number
County:		GWICK	NW 1/2	· · · · · · · · · · · · · · · · · · ·	NW 1/4	<u> </u>	T 28	S	R 1 E E/W/
		from nearest to t Anita	-	nddress of well if locat nita, Kansas	ed within city?				
2 WATER	WELL OW	/NER:	Don Brazel	.1					
RR#, St. A			1909 W. An	ita	Board of Agriculture, Division of Water Resources				
City, State,		:	Wichita, K	Cansas			Application N	lumber:	
LOCATE	WELL'S L	OCATION WITH			40	ft. ELEVA	TION:		
-¹ AN "X" I	IN SECTIO	N BOX:	Depth(s) Ground	water Encountered	1	1,6 ft. :	2 <i></i>	ft. 3.	. , . , . ,
т Г	1		WELL'S STATIC	WATER LEVEL .16	ft. b	elow land sur	face measured on m	o/day/yr	11-29-83
I I	1		Ti and the second secon						nping gpm
NW NE Est. Yield gpm: Well water was ft. after hours pumping									
₩ W -	1			TO BE USED AS:		5 Public water supply 8 Air condition			njection well
7	I CVA	<u> </u>	1_Domestic	3 Feedlot	6 Oil field wat	ter supply	9 Dewatering	12 C	other (Specify below)
-	- 2W	SE	2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Observation well		
l L	i	1	Was a chemical/	bacteriological sample	submitted to De	epartment? Y	esNoX	; If yes, ı	mo/day/yr sample was sub-
<u> </u>		5	mitted			Wa	ter Well Disinfected?		
5 TYPE O	F BLANK (CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINT	rs: Glued	XClamped
1 Ste	el	3 <u>RMP (S</u>	R)	6 Asbestos-Cement		(specify below			d
2 PV		4 ABS		7 Fiberglass		-			led
									n. to ft.
	_			.in., weight	1 . 59.		ft. Wall thickness or	gauge No	. 2.03
TYPE OF S	SCREEN O	R PERFORATIO	N MATERIAL:		7 PV	С	10 Asbes	tos-cemer	t
1 Ste	ei	3 Stainles	s steel	5 Fiberglass	8 <u>RM</u>	IP (SR)	11 Other	(specify) .	
2 Bra	ISS	4 Galvania	zed steel	6 Concrete tile	9 AB	S	12 None	used (ope	n hole)
SCREEN C	OR PERFOR	RATION OPENIN	IGS ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Lou	vered shut	ter 4 K	ey punched	7 Torc			· · · · · · · · · · · · · · · · · · ·		
SCREEN-P	PERFORATI	ED INTERVALS:							
G	RAVEL PA	CK INTERVALS:							
T :		· · · · · · · · · · · · · · · · · · ·	From	14 ft. to	140	ft., Fro			
6 GROUT				2 Cement grout	3 Bento		=		
Grout Interv				From	ft.				. ft. to
		ource of possible					tock pens		andoned water well
1 Septic tank 4 Later				7 Pit privy			• -	15 Oil well/Gas well	
2 Sewer lines 5 Cess				8 Sewage lag	goon				
		er lines 6 Seep	age pit	9 Feedyard			•	NONE	APPARENT
Direction from	TO TO		LITHOLOGIC	100	FROM	How ma		THOLOGIC	2106
0	3	Topsoil	LITTIOLOGIC	LOG	FROW	10		HOLOGI	J LOG
3	7	Clay							
7	56	Brown Sha	16						
56	115	Gray Shal							
115	140		le & Limest	one					
	1.0	oray bilas	to a Hillion						
							 		
-									
					1				

						(2)			
									r my jurisdiction and was
completed on (mo/day/year) 12-2-83									
under the b	DUSINESS NA	me of fiall	NETT & LA	mp Service, II	nd PRINT clear	by (signa v. Please fill in	ture Dake n blanks, underline of	circle the	correct answers. Send top
three copies	s to Kansas	Department of H	ealth and Environ	ment, Division of Enviro	nment, Environi	mental Geolog	gy Section, Topeka, K	S 66620. S	Send one to WATER WELL
OWNER at	nd retain or	ne for your recor	ds.	,			' '		