

MW-62111024

WATER WELL RECORDForm WWC-5KSA 82a-1212

1

LOCATION OF WATER WELL:

County: Sedgwick

Distance and direction from nearest town or city street address of well if located within city?
2464 S. Glenn; Truesdell Middle School

Fraction

SW $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$

Section Number

6

Township Number

T 28 S

Range Number

R 1 E/W

2

WATER WELL OWNER:

RR#, St. Address, Box # :
USD 259 3850 N Hydraulic

City, State, ZIP Code :
Wichita KS 67219

Board of Agriculture, Division of Water Resources
Application Number:

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

E

S

NW

NE

SW

SE

4

DEPTH OF COMPLETED WELL: 18 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 10.68 ft. below land surface measured on mo/day/yr 10-6-93

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 2 in. to ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 7 ft. to 18 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6

GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 7 ft. to 1 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? N How many feet? 400

FROM

TO

LITHOLOGIC LOG

FROM

TO

PLUGGING INTERVALS

0.0

3.0

Top Soil

3.0

7.0

Silt, very clayey

7.0

12.0

Silt, very clayey

12.0

13.0

Sand, very coarse

13.0

18.0

Sand & gravel

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-8-93 under the business name of GSI by (signature) Alison Truitt

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

H

EW

SEC

1/4

1/4

1/4