

MW-7		2111024		WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4 NW 1/4 NE 1/4		6		T 28 S		R 1 E	
Distance and direction from nearest town or city street address of well if located within city?									
2464 S. Glenn; Truesdell Middle School									
2 WATER WELL OWNER:		USD 259		3850 N. Hydraulic		Wichita KS 67219		Board of Agriculture, Division of Water Resources	
RR#, St. Address, Box #		City, State, ZIP Code		Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18 ft.		ELEVATION:					
		Depth(s) Groundwater Encountered 1 10 ft. 2 ft. 3 ft.		WELL'S STATIC WATER LEVEL 10.60 ft. below land surface measured on mo/day/yr 10-6-93					
		Pump test data: Well water was ft. after hours pumping gpm		Est. Yield gpm Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 8 in. to ft. and in. to ft.		WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below)		Welded					
2 PVC 4 ABS		7 Fiberglass		Threaded Flush					
Blank casing diameter 2 in. to ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154							
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)							
2 Louvered shutter 4 Key punched									
SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft.		From ft. to ft.							
GRAVEL PACK INTERVALS: From 7 ft. to 18 ft.		From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 7 ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? NW		How many feet? 300							
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS							
0.0 3.0 Top soil									
3.0 9.0 Silt, very clayey									
9.0 12.5 Sand, very fine to fine									
12.5 18.0 Sand, very coarse									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed 2 reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-93 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-8-93									
under the business name of GSI by (signature) Allison Irwin									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									