


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: NE 1/4 NE 1/4 NE 1/4	Section Number: 7	Township Number: T 28 S	Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city? AMOCO #5460 3201 S. SENECA, WICHITA, KS 67217					
2 WATER WELL OWNER: AMOCO OIL COMPANY RR#, St. Address, Box #: 8700 INDIAN CREEK PKWAY City, State, ZIP Code: OVERLAND PARK, KS 66210			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 30.0 ft. ELEVATION: Depth(s) Groundwater Encountered: 1 13.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 13.0 ft. below land surface measured on mo/day/yr 3-1-91 Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 1/4 in. to 30.0 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well RECOVERY WELL Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter: 6 in. to 10.0 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: in., weight lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30.0 ft. to 10.0 ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 7.0 ft. to 5.8 ft., From 5.0 ft. to X ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) FUEL TANKS Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0 6" CONCRETE					
6" 1 FILL					
1 5 CLAY, MED, GRAY, MOIST					
5 14 SAND, MED BROWN, MOIST					
14 19 SAND, MED BROWN, WET					
19 24 SAND, MED BROWN, WET					
24 30 SAND, COARSE, BROWN, WET					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-1-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 519 This Water Well Record was completed on (mo/day/yr) MAY 17 1991 under the business name of WESTAERMAAT DRILLING by (signature) Ray V. Jones					