

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW ¼ NE ¼ SW ¼	Section Number 11	Township Number T 28 S	Range Number R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? Kansas Turnpike @ K-15, Wichita					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Boeing PO Box 1730 Wichita KS 67277-1730 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 15 ft.			
		Depth(s) Groundwater Encountered 1. 15 ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 15.84 ft. below land surface measured on mo/day/yr 8-23-93			
		Pump test data: Well water was .ft. after . hours pumping gpm			
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm			
		Bore Hole Diameter 8 in. to .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No X.....; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . Clamped .
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded .
Blank casing diameter 2 in. to .ft., Dia .		7 Fiberglass	Threaded Flush		
Casing height above land surface 36 in., weight 93 lbs./ft. Wall thickness or gauge No. Sched 80					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) .
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot		6 Wire wrapped	9 Drilled holes		
2 Louvered shutter		7 Torch cut	10 Other (specify) .		
4 Key punched					
SCREEN-PERFORATED INTERVALS: From 10 ft. to 30 ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From 9 ft. to 30 ft., From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 9 ft. to 1 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? NA		How many feet? NA			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	Top soil, brown, clayey, silty			
0.5	10.0	Silt, rust, sandy, clayey			
10.0	26.5	Sand			
26.5	29.5	Shale, olive green			
29.5	30.0	Shale, dark bluish gray			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-23-93 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 531		This Water Well Record was completed on (mo/day/yr) 8-26-93		by signature Allison Irwin	
under the business name of GSI					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.