

MW-154 211041 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NE 1/4 SW 1/4 Section Number: 11 Township Number: T 28 S Range Number: R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? Kansas Turnpike & K-15, Wichita

2 WATER WELL OWNER: RR#, St. Address, Box #: Boeing PO Box 7730 City, State, ZIP Code: Wichita KS 67277-7730 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in SW quadrant]

4 DEPTH OF COMPLETED WELL: 24 ft. ELEVATION: 13 ft. 13 Depth(s) Groundwater Encountered: 13 ft. 13 WELL'S STATIC WATER LEVEL: 13.00 ft. below land surface measured on mo/day/yr 8-19-93

Pump test data: Well water was ... ft. after ... hours pumping ... gpm

Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm

Bore Hole Diameter: 8 in. to ... ft., and ... in. to ... ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes ... No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ... No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ... Clamped ... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ... Threaded Flush

Blank casing diameter: 2 in. to ... ft., Dia ... in. to ... ft., Dia ... in. to ... ft.

Casing height above land surface: 36 in., weight: 93 lbs./ft. Wall thickness or gauge No. Schd 80

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut

SCREEN-PERFORATED INTERVALS: From 9 ft. to 24 ft. From ... ft. to ... ft.

GRAVEL PACK INTERVALS: From 8 ft. to 24 ft. From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 8 ft. to 1 ft. From ... ft. to ... ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NA

Direction from well? NA How many feet? NA

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0.0 0.5 Top soil, brown

0.5 7.0 Silt, light brown, clayey

7.0 10.0 Sand, tan

10.0 17.0 Sand, tan

17.0 24.5 Shale, olive green

24.5 25.0 Shale, dark bluish gray

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-19-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 8-26-93 under the business name of BSI by (signature) Allison Irwin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4