

[1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SW ¼ SE ¼ NE ¼ EW	11	T 28 S R 1		
Distance and direction from nearest town or city street address of well if located within city? Plant 1 2200' SW from the intersection of 31st South and Oliver, Wichita, KS 52905009 MW-74					
[2] WATER WELL OWNER: Boeing Military Airplanes	Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box #: P.O. Box 7730, M/S K11-65	Application Number:				
City, State, ZIP Code : Wichita, KS 67277-7730					
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	[4] DEPTH OF COMPLETED WELL..... 43.5 ft. ELEVATION: Approx., Surface Elev.: .. 1354.6				
N S	Depth(s) Groundwater Encountered 1..19...ft. 2....ft. 3....ft. WELL'S STATIC WATER LEVEL ... 5.2 ft. below land surface measured on mo/day/yr Q6/28/90. Pump test data: Well water was ft. after hours pumping gpm Est. Yield . N/A. . . gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter... 9in. to 43.5ft., andin. toft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No X..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
[5] TYPE OF BLANK CASING USED:	CASING JOINTS: Glued Clamped Welded Threaded X				
1 Steel (2) PVC Blank casing diameter 2in. to 8.0ft., Diain. toft., Diain. toft. Casing height above land surface..... 35.4in., weight lbs./ft. Wall thickness or gauge No. Schedule 40	3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)				
TYPE OF SCREEN OR PERFORATION MATERIAL:	(7) PVC 10 Asbestos-cement				
1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter	3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 Gauzed wrapped 8 Wire wrapped 9 Torch cut 10 Saw cut 11 None (open hole)				
SCREEN-PERFORATED INTERVALS:	From 8.0 ft. to 43.0 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS:	From 6.5 ft. to 43.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
[6] GROUT MATERIAL:	1 Neat cement (2) Cement grout (3) Bentonite 4 Other				
GROUT INTERVALS: FROM 0 ft. to 4.0 ft. FROM 4.0 ft. to 6.5 ft. FROM ft. to ft.					
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well (16) Other (specify below) Industrial Warehouse				
Direction from well? North	How many feet? 45				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.5	Fill			
3.5	6.0	Silty Lean Clay, Dark Brown			
6.0	12.0	Lean Clay, Olive-Gray			
12.0	20.0	Fat Clay, Red-Brown			
20.0	31.5	Lean to Fat Clay, Olive-Gray			
31.5	32.0	Limestone			
32.0	43.0	Fat Clay, Olive-Gray			
43.0	43.5	Shale, Dark Gray			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/04/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 12/13/90 by signature Terracon Consultants, Inc.					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.