

1 LOCATION OF WATER WELL:		Fraction	NE NW NE	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 NW 1/4 SW 1/4	# 21	T 28 S	R 1	EW
Distance and direction from nearest town or city street address of well if located within city? 1131 EAST 47th STREET SOUTH, WICHITA, KS.						
2 WATER WELL OWNER: COASTAL MART						
RR#, St. Address, Box # : P.O. BOX 1030						
City, State, ZIP Code : WICHITA, KANSAS						
Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17.7 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 12.6 ft. below land surface measured on mo/day/yr 9/20/90				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield 4 gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 4 in. to 18 in. to ft.				
WELL WATER TO BE USED AS: 12 5 Public water supply 8 Air conditioning 11 Injection well						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering #1 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
7 Fiberglass Threaded X						
Blank casing diameter 4 in. to 7.7 ft. Dia. in. to ft. Dia. in. to ft.						
Casing height above land surface FLUSH MOUNT in. weight lbs./ft. Wall thickness or gauge No. 154						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)						
12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
3 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 7.7 ft. to 17.7 ft. From ft. to ft.						
From ft. to ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 6 ft. to 17.7 ft. From ft. to ft.						
From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL:						
1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 17.2 ft. to 6 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage SW 16 Other (specify below)						
Direction from well? NORTH How many feet? 25'						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4"	CONCRETE PAVEMENT				
4"	4'	SILTY SAND, V. DK BR				
4'	5'	SILT, STRONG BR				
5'	8'	SAND, FINE-MED GRAINED, P GRADED				
8'	18'	SAND, COARSE GRAINED, W GRADED				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/20/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10/25/90 under the business name of GEOTECHNICAL SERVICES INC by (signature) Dorinda Hinde-Wallace						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4