


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 SE 1/4 NE 1/4	11	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1,900' S from the intersection of 31st Street South & Oliver, Wichita, KS 52905009 MW-64					
2 WATER WELL OWNER: Boeing Military Airplanes RR#, St. Address, Box #: P. O. Box 7730 M/S K11-65 City, State, ZIP Code: Wichita, KS 67277-7730 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50.0 ft. ELEVATION: Approx. Surface Elev: 1362.7			
		Depth(s) Groundwater Encountered 1 20 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 7.6 ft. below land surface measured on mo/day/yr 03/15/90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 11 in. to 50.0 ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded		2 PVC 4 ABS 7 Fiberglass Threaded X			
Blank casing diameter 4 in. to 20.0 ft. Dia in. to ft.		Casing height above land surface 40.4 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 20.0 ft. to 49.5 ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 19.0 ft. to 50.0 ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 17.0 ft. From 17.0 ft. to 19.0 ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Industrial Plant		Direction from well? W How many feet? 50			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.0	Dark Brown Fill, Lean to Fat Clay			
3.0	16.0	Light Red-Brown Fat to Lean Clay			
16.0	21.0	Red-Brown Fat Clay			
21.0	47.0	Olive-Gray Fat Clay			
47.0	50.0	Dark Gray Weathered Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 02/14/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 5-9-90 under the business name of Terracon Consultants, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

F/W

SEC.

1/4

1/4

1/4