

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>SW 1/4 SE 1/4 SW 1/4</u>	Section Number <u>11</u>	Township Number <u>T 28 S</u>	Range Number <u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>K-15 and MacArthur Road, Wichita, KS</u>					
2 WATER WELL OWNER: <u>The Boeing Co.</u> RR#, St. Address, Box #: <u>P.O. Box 7730</u> City, State, ZIP Code: <u>Wichita, KS 67277</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>58</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>30</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>12.5</u> in. to <u>50</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Recovery (RW-28A)</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
				8 Concrete tile	
				9 Other (specify below)	
				CASING JOINTS: Glued Clamped	
				Welded	
				Threaded. <u>X</u>	
Blank casing diameter <u>5</u> in. to <u>24</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface: <u>10</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sch. 80</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				7 Torch cut	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From <u>24</u> ft. to <u>49</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>21</u> ft. to <u>50</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>Bentonite - Grout</u>					
Grout Intervals: From <u>3</u> ft. to <u>19</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				<u>Unknown</u>	
Direction from well?				How many feet?	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay - dark brown (fill)	41	48	Weathered Shale - mottled olive yellow-brown, red brown
3	9	Clay - mottled brown, yellow-brown, gray	48	50	Weathered Gray Shale
9	24	Clay - brown mottled dk. brown			
24	29	Sandy Clay - brown mottled dark brown			
29	33	Sand - pale brown, fine to coarse			
33	41	Sand - pale brown, coarse to very coarse			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10/12/92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>471</u> This Water Well Record was completed on (mo/day/yr) <u>11/3/92</u> under the business name of <u>HWS Technologies</u> by (signature) <u>[Signature]</u>					