

1 LOCATION OF WATER WELL: County: Sedgwick NW 1/4 SW 1/4 SE 1/4 11 Township Number 28 S Range Number 1 E/W

Distance and direction from nearest town or city/street address of well if located within city?
K-15 and MacArthur Road, Wichita, KS

2 WATER WELL OWNER: The Boeing Co
RR#, St. Address, Box #: P.O. Box 7730
City, State, ZIP Code: Wichita, KS 67277

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 36 ft. ft. ELEVATION: NA ft.
Depth(s) Groundwater Encountered 1. 15 ft. 2. 10/25/92 ft. 3. 10/25/92 ft.
WELL'S STATIC WATER LEVEL 18.3 ft. below land surface measured on mo/day/yr 10/25/92
Pump test data: Well water was 35.5 ft. after 5 hours pumping 8 gpm
Est. Yield 125 gpm: Well water was 35.5 ft. after 5 hours pumping 8 gpm
Bore Hole Diameter 12.5 in. to 36 ft., and 36 in. to 36 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recovery (ISA)
Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 Brass 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
3 PVC 7 Fiberglass Threaded X
Blank casing diameter 5 in. to 15 ft., Dia 5 in. to 15 ft., Dia 5 in. to 15 ft.
Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 52, 80
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 15 ft. to 35 ft., From 15 ft. to 35 ft., From 15 ft. to 35 ft.
GRAVEL PACK INTERVALS: From 12 ft. to 36 ft., From 12 ft. to 36 ft., From 12 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite grout
Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Unknown
Direction from well? How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/25/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 10/25/92 under the business name of HWS Technologies by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.