


MW-149 2011065		WATER WELL RECORD		Form WWC-5	KSA 82a-1212																																																	
1 LOCATION OF WELL:		Fraction	Section Number	Township Number		Range Number																																																
County: <u>Sedgwick</u>		<u>NE 1/4 SE 1/4 SE 1/4</u>	<u>11</u>	T <u>28</u> S		R <u>1</u> <u>EW</u>																																																
Distance and direction from nearest town or city street address of well if located within city? <u>Plant 2 - Boeing</u>																																																						
2 WATER WELL OWNER: <u>Boeing</u> RR#, St. Address, Box #: <u>PO Box 7730</u> City, State, ZIP Code: <u>Wichita KS 67277-7730</u> Board of Agriculture, Division of Water Resources Application Number:																																																						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>6.3</u> ft. ELEVATION:																																																				
		Depth(s) Groundwater Encountered 1. <u>34</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>21.28</u> ft. below land surface measured on mo/day/yr <u>3-11-93</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>																																																				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> <u>4 ABS</u> 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to ft., Dia. in. to ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>Flush</u> in., weight <u>70.3</u> lbs./ft. Wall thickness or gauge No. <u>154</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>23</u> ft. to <u>63</u> ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>63</u> ft., From ft. to ft., From ft. to ft.																																																						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>22</u> ft. to <u>1</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>NA</u> How many feet? <u>NA</u>																																																						
<table border="1"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0.0</td><td>0.5</td><td>Concrete</td><td></td><td></td><td></td></tr><tr><td>0.5</td><td>1.5</td><td>fill sand</td><td></td><td></td><td></td></tr><tr><td>1.5</td><td>12.0</td><td>Silty clay</td><td></td><td></td><td></td></tr><tr><td>12.0</td><td>52.0</td><td>Clay, increasing sand with depth</td><td></td><td></td><td></td></tr><tr><td>52.0</td><td>59.0</td><td>Sand, silty, sandy</td><td></td><td></td><td></td></tr><tr><td>59.0</td><td>62.0</td><td>clay, weathered</td><td></td><td></td><td></td></tr><tr><td>62.0</td><td>63.0</td><td>Shale, wellington</td><td></td><td></td><td></td></tr></tbody></table> <u>Flush mount waiver granted Boeing by Don Taylor 12-22-92 for</u>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0.0	0.5	Concrete				0.5	1.5	fill sand				1.5	12.0	Silty clay				12.0	52.0	Clay, increasing sand with depth				52.0	59.0	Sand, silty, sandy				59.0	62.0	clay, weathered				62.0	63.0	Shale, wellington			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																	
0.0	0.5	Concrete																																																				
0.5	1.5	fill sand																																																				
1.5	12.0	Silty clay																																																				
12.0	52.0	Clay, increasing sand with depth																																																				
52.0	59.0	Sand, silty, sandy																																																				
59.0	62.0	clay, weathered																																																				
62.0	63.0	Shale, wellington																																																				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-13-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>4-7-93</u> under the business name of <u>GSI</u> by (signature) <u>Allison Irwin</u>																																																						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.