


1 LOCATION OF WATER WELL: Fraction $5\frac{1}{4}$ SE $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 11 Township Number T 28 S Range Number R 1 E/W
County: Sedgwick Distance and direction from nearest town or city street address of well if located within city?

East of Security Bldg outside Plant II

2 WATER WELL OWNER: RR#, St. Address, Box #: Boeing PO Box 7730 City, State, ZIP Code: Wichita KS 67277-7730 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 61 ft. ELEVATION: 36.5 ft.



Depth(s) Groundwater Encountered 1. 36.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 37.35 ft. below land surface measured on mo/day/yr 1-9-93

Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush

Blank casing diameter 2 in. to ft. Dia 703 in. to ft. Dia 154 in. to ft. Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No. 154

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 21 ft. to 61 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 61 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 20 ft. to 1 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NA

Direction from well? NA How many feet? NA

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0.0 0.5 Concrete

0.5 7.5 Clay, brown

7.5 29.0 Clay, reddish brown

29.0 51.5 Clay, brown

51.5 58.5 Clay, olive green

58.0 61.0 Shale

Flush mount waiver granted 12-22-92 for Boeing by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-11-93 and this record is true to the best of my knowledge and belief. Kansas

Water Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 4-7-93 under the business name of GST by (signature) Allison