

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 NW 1/4 NW 1/4		Section Number 12	Township Number T 28 S	Range Number R 1
Distance and direction from nearest town or city street address of well if located within city? 1,000' SE of the intersection of Oliver & 31st Street South, Wichita, KS				Flight Line Monitor Wells 52915060 MW-98		
2 WATER WELL OWNER: Boeing Military Airplanes RR#, St. Address, Box # : P. O. Box 7730 M/S K11-65 City, State, ZIP Code : Wichita, KS 67277-7730				Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: Approx Surf. Elev: 1352.2 Depth(s) Groundwater Encountered 1. 23 ft. 2. 3. ft. 3. ft. WELL'S STATIC WATER LEVEL 20.3 ft. below land surface measured on mo/day/yr 06/04/91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 35 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2 in. to 14.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 36.5 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 8 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		7 PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 34.5 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 12.5 ft. to 35.0 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 35 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Industrial Facility				
Direction from well? West		How many feet? 1,000				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
			0	35.0	Bentonite-Cement Grout Casing was removed	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/21/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 8-5-91 under the business name of Terracon Consultants, Inc. by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						