

1 LOCATION OF WATER WELL:
 County: Sedgwick Fraction SE 1/4 NW 1/4 SW 1/4 Section Number 12 Township Number T 28 S Range Number R 1 E/W
 Distance and direction from nearest town or city street address of well if located within city?
Bldg L-23, Boeing, Wichita KS

2 WATER WELL OWNER:
 RR#, St. Address, Box # : Boeing P.O. Box 7730
 City, State, ZIP Code : Wichita KS 67277-7730
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N							
W	<table border="1"> <tr> <td>NW</td> <td>NE</td> </tr> <tr> <td>SW</td> <td>SE</td> </tr> </table>	NW	NE	SW	SE	E	
NW	NE						
SW	SE						
S							

4 DEPTH OF COMPLETED WELL: 59 ft. ELEVATION: NA
 Depth(s) Groundwater Encountered 1. NA ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr NA
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 8 in. to ft. and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Soil Vapor Extraction
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 12 in., weight 703 lbs./ft. Wall thickness or gauge No. 154
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 8.98 ft. to 58.98 ft. From ft. to ft. From ft. to ft.
 From ft. to ft. From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 7.98 ft. to 58.98 ft. From ft. to ft. From ft. to ft.
 From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:
 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 7.98 ft. to 0.0 ft. From ft. to ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage NA
 Direction from well? NA How many feet? NA

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	4.0	Clay, Silty			
4.0	7.0	Clay			
7.0	13.0	Clay, Sandy			
13.0	19.0	Clay, Slightly Silty			
19.0	29.0	Clay, very sandy			
29.0	34.0	Sand, med. well sorted			
34.0	39.0	Clay, Sandy			
39.0	44.0	Sand, med. well sorted			
44.0	49.0	Clayey Sand, med. well sorted			
49.0	59.0	Shale, weathered, soft			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-19-92 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-23-92
 under the business name of Geotechnical Services, Inc. by (signature) Allison J. Iwen