

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Distance and direction from nearest town or city street address of well if located within city?	Fraction <u>SW 1/4 NE 1/4 SW 1/4</u>	Section Number <u>13</u>	Township Number <u>T 28 S</u>	Range Number <u>R 1 E</u>
---	---	-----------------------------	----------------------------------	------------------------------

2 WATER WELL OWNER: McConnell AFB
RR#, St. Address, Box # :
City, State, ZIP Code : Wichita, Kansas
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL... 24.5 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 10.0 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 9.73 ft. below land surface measured on mo/day/yr 12/5/88
Pump test data: Well water was ft. after hours pumping
Est. Yield gpm: Well water was ft. after hours pumping
Bore Hole Diameter 1.1 in. to 24.5 ft., and in. to
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 2 in. to 9.5 ft., Dia in. to ft., Dia in. to
Casing height above land surface 0.2 in., weight lbs./ft. Wall thickness or gauge No. 5.4 H.P.
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 9.5 ft. to 23.5 ft., From ft. to
From ft. to ft., From ft. to
GRAVEL PACK INTERVALS: From 6.0 ft. to 24.5 ft., From ft. to
From ft. to ft., From ft. to
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement/Bentonite Grout
Grout intervals: From 2.0 ft. to 3.5 ft., From 3.5 ft. to 4.0 ft., From ft. to
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage None
Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.0	Soil - DK Bn Cl Day			
1.0	6.0	Clay - Bn Si			
6.0	11.5	" - IAM " Moist			
11.5	15.0	" - LTIAM " Saturated			
15.0	24.5	" - " " "			

RECEIVED RECEIVED RECEIVED
MAR 05 1990 JUN 15 1989 OCT 27 1989
DIVISION OF ENVIRONMENT DIVISION OF ENVIRONMENT DIVISION OF ENVIRONMENT

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and completed on (mo/day/year) 11/17/88 and this record is true to the best of my knowledge and belief. Kar
Water Well Contractor's License No. 494 This Water Well Record was completed on (mo/day/yr) 11/30/88
Under the business name of Southwestern Lab Inc by (signature) Robert S. Jurek
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.