

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgwick</u>		NW 1/4 SW 1/4 NW 1/4		13		T 28 S		R 1 <u>EW</u>	
Distance and direction from nearest town or city street address of well if located within city?									
<u>560 Feet East, 1930 Feet South of Oliver and MacArthur, Wichita, Kansas</u>									
2 WATER WELL OWNER:		Boeing Commercial Airplane Group							
RR#, St. Address, Box # :		P.O. Box 7730							
City, State, ZIP Code :		Wichita, Kansas 67277-7730							
		Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 9 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 6.65 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 7 7/8 in. to 42 ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No ☒							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded ☒							
Blank casing diameter 2 in. to 7 ft. Dia		in. to ft. Dia in. to ft.							
Casing height above land surface 36 in. weight		lbs./ft. Wall thickness or gauge No. Sch. 80							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)							
2 Louvered shutter 4 Key punched 7 Torch cut									
SCREEN-PERFORATED INTERVALS:		From 7 ft. to 42 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 6 ft. to 42 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 1.5 ft. to 6 ft. From Surf. ft. to 1.5 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 100							
Direction from well? west									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	3	Dark brown clay	36	37	Gray green clay				
3	5	Red brown, silty clay	37	40	Olive gray shale				
5	10	Brown, silty to sandy clay	40	42	Dark gray shale				
10	12	Dark brown silty clay							
12	17	Gray brown silty clay							
17	20	Red brown silty clay							
20	25	Yellow brown silty clay			MW130				
25	30	Gray green silty clay							
30	36	Yellow brown clay							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-10-92 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 01-11-93									
under the business name of GeoCore Services, Inc. by (signature) Dale A. Robb									