

1 LOCATION OF WATER WELL: Sedgwick		Fraction SW 1/4 SW 1/4 NW 1/4		Section Number 13	Township Number T 28 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 560 Feet East, 2040 Feet South of Oliver & MacArthur, Wichita, Kansas						
2 WATER WELL OWNER: Boeing Commercial Airplane Group RR#, St. Address, Box #: P.O. Box 7730 City, State, ZIP Code: Wichita, Kansas 67277-7730 Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 39 ft. ELEVATION: 10 ft.				
		Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8 in. to 39 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 6 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 33 in., weight lbs./ft. Wall thickness or gauge No. Sch. 80 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 6 ft. to 36 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 5 ft. to 39 ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 1 1/2 ft. to 5 ft., From Surf. ft. to 1 1/2 ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? west How many feet? 100						
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS
0	2	Dark brown silty clay				MW131
2	5.5	Red brown, silty clay				
5.5	8	Brown silty clay				
8	8.5	Gravel (fill)				
8.5	12	Dark brown silty clay				
12	25	Brown silty to sandy clay				
25	35	Gray green clay				
35	37	Olive gray shale				
37	39	Dark gray shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 12-09-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 01-11-93 under the business name of GeoCore Services, Inc. by (signature) Dale A. Bell						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						