

1 LOCATION OF WATER WELL:		Fraction SE 1/4 NE 1/4 NW 1/4		Section Number 14		Township Number T 28 S		Range Number R 1 EXX	
County: <u>Sedgwick</u>									
Distance and direction from nearest town or city street address of well if located within city? <u>Approximately 1/8 mile south and 1/8 mile east of Wichita</u>									
2 WATER WELL OWNER:		Boeing Company				Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		3801 S. Oliver				Application Number: <u>N/A</u>			
City, State, ZIP Code :		Wichita, KS 67210							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 31 ft. ELEVATION: unknown							
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL ... 9.6 ... ft. below land surface measured on mo/day/yr ... 8-25-92							
		Pump test data: Well water was not ch'd. ft. after hours pumping gpm							
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter ... 11 ... in. to ... 31 ... ft., and ... in. to ... ft.							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded ☐							
2 PVC 4 ABS		7 Fiberglass Threaded ☐							
Blank casing diameter 5 ... in. to ... 12 ... ft., Dia. in. to ... ft., Dia. in. to ... ft.									
Casing height above land surface 24 ... in., weight 2.87 ... lbs./ft. Wall thickness or gauge No. 265									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot		6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched		7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 12 ... ft. to 29 ... ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From 10 ... ft. to 31 ... ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug							
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ... ft. to 10 ... ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy		10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon		11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		12 Fertilizer storage 16 Other (specify below)							
		13 Insecticide storage Ground already contaminated							
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 Topsoil									
1 8 Clay, tan with caliche									
8 13 Clay, tan, sandy with sand mixed									
13 15 Sand, fine, some gravel, fine with clay streaks									
15 18 Clay, light tan									
18 18.5 Sand, fine, loose									
18.5 20.25 Sand, fine to medium with medium to coarse cobble and clay mixed, tight									
20.25 20.5 Cemented sand, hard									
20.5 28 Clay, green, yellow, red									
28 31 Shale, gray, soft									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-22-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 2-24-93 under the business name of <u>Clarke Well & Equipment, Inc.</u> by (signature) <u>Clarke Well & Equipment, Inc.</u>									