


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		NW 1/4 NE 1/4 SW 1/4	14	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? <u>West of K-15, 2750 Feet South of MacArthur, Wichita, Kansas</u>					
2 WATER WELL OWNER:		Boeing Commercial Airplane Group			
RR#, St. Address, Box # :		P.O. Box 7730			
City, State, ZIP Code :		Wichita, Kansas 67277-7730			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 44 ft.			
		Depth(s) Groundwater Encountered 1. 44 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 41.1 ft. below land surface measured on mo/day/yr 12-10-92			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 7/8 in. to 55 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)					
Blank casing diameter 2 in. to 30 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 30 ft. to 55 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 28 ft. to 55 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 26 ft. to 28 ft., From Surf ft. to 26 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Boeing industrial plant					
Direction from well? northeast		How many feet? 4000			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Dark brown-red brown clay			MW123
2	20	Red brown, silty clay			
20	25	Red silty clay			
25	27	Red brown silty clay			
27	30	Red silty clay			
30	35	Fine to coarse sand-tan to red			
35	50	Sand-fine to coarse grain/gravel			
50	52	Olive gray weathered shale			
52	55	Dark gray shale, gypsum lense			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-02-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 01-09-93 under the business name of GeoCore Services, Inc. by (signature) Dan A. Polk					