

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NW 1/4 NE 1/4		Section Number 14	Township Number T 28 S	Range Number R 1 E E/W
Distance and direction from nearest town or city street address of well if located within city? Aprox 1680' West of Oliver Aprox 880' South of MacArthur, Wichita, Kansas Project No. 52915111						
2 WATER WELL OWNER: Boeing Commercial Airplane Group RR#, St. Address, Box # : P.O. Box 7730 M/S K11-65 City, State, ZIP Code : Wichita, Kansas 67277-7730				MW-23 Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 1 Mile N W E S NW NE SW SE X		4 DEPTH OF COMPLETED WELL..... 30.58 .. ft. ELEVATION: .. 1337.7 AP..... Depth(s) Groundwater Encountered 1..... 25.98 ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL .. 25.98 .. ft. below land surface measured on mo/day/yr .. 2/14/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield .. NA .. gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. . . NA . . in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.. NA.....No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes NA No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 4"..... in. to .. 30.58 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface..... 36..... in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: NA 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: NA 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From .. NA ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From .. NA ft. to ft., From ft. to ft.		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 6 Saw cut 11 None (open hole) 7 Drilled holes 10 Other (specify)				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From .. 24 ft. to 0 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Industrial Plant Direction from well? How many feet?		13 Insecticide storage				
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
		0 24.0 Cement Grout				
		24.0 30.0 Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/14/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 2/26/92 under the business name of Terracon Consultants by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						