

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																			
County: Sedgwick		SW 1/4 NW 1/4 NE 1/4		14		T 28 S		R 1																			
Distance and direction from nearest town or city street address of well if located within city?																											
610' S of 4141 East MacArthur Road, Wichita, KS						52895054		PSMW-8																			
2 WATER WELL OWNER: Boeing Military Airplanes																											
RR#, St. Address, Box # : P. O. Box 7730 M/S K06-00						Board of Agriculture, Division of Water Resources																					
City, State, ZIP Code : Wichita, KS 67277-7730						Application Number:																					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 43.5 ft. ELEVATION: Approx. Surface Elev: 1328.4' MSL																									
		Depth(s) Groundwater Encountered 1. 23.5 ft. 2. ft. 3. ft.																									
		WELL'S STATIC WATER LEVEL 13.8 ft. below land surface measured on mo/day/yr 09/21/89																									
		Pump test data: Well water was ft. after hours pumping gpm																									
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm																									
		Bore Hole Diameter 9 in. to 43.5 ft., and in. to ft.																									
WELL WATER TO BE USED AS:																											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																											
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted																											
Water Well Disinfected? Yes No X																											
5 TYPE OF BLANK CASING USED:																											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.																											
TYPE OF SCREEN OR PERFORATION MATERIAL:																											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 9 ABS 12 None used (open hole)																											
SCREEN OR PERFORATION OPENINGS ARE:																											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.																											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																											
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.																											
What is the nearest source of possible contamination:																											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? - 13 Insecticide storage Salvage Yard																											
How many feet? 0																											
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td>20</td> <td>0</td> <td>Bentonite-Cement Grout</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Well casing was removed to a depth of 20 feet by re-drilling; boring was subsequently plugged with bentonite-cement grout.</td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				20	0	Bentonite-Cement Grout						Well casing was removed to a depth of 20 feet by re-drilling; boring was subsequently plugged with bentonite-cement grout.
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																						
			20	0	Bentonite-Cement Grout																						
					Well casing was removed to a depth of 20 feet by re-drilling; boring was subsequently plugged with bentonite-cement grout.																						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/27/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 12/29/90 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer																											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																											